

Overview

HP FlexFabric 11900 Switch Series

Models

HP FlexFabric 11908-V Switch Chassis

JG608A

Key features

- High-performance CLOS-based switching architecture
- Large layer 2 scaling with TRILL and HP IRF
- Feature-rich routing with IPv4/IPv6, MPLS, and QoS
- Enhanced modularity with control and data plane separation
- High 10GbE and 40GbE density; 100GbE ready across 7.7 Tb/s switch fabric

Product overview

The HP FlexFabric 11900 Switch Series is a high-performance data center aggregation switch that provides line-rate, high-density 10GbE and 40GbE connectivity designed for cost-effective end-of-row (EoR) and small core deployments.

With latency as low as 3 μ s, the HP FlexFabric 11900 Switch Series can scale to 384 1/10GbE, 192 1/10GBASE-T, 64 40GbE or 16 100GbE ports. The switch delivers up to 7.7 Tbps switching capacity and 5.8 Bpps forwarding throughput. A broad variety of interface options is available, including 1/10GbE, 1/10GBASE-T, 40GbE and 100GbE.

Ready for software-defined networking (SDN), the switch supports full Layer 2 and 3 features, including advanced features such as transparent Interconnection of Lots of Links (TRILL) and Intelligent Resilient Framework (IRF), which provides the ability to build large, resilient switching fabrics. The HP FlexFabric 11900 Switch Series also supports fully redundant and hot-swappable components to complement its other enterprise-class capabilities.

Features and benefits

Data center optimized

- **Scalable Layer 2 fabrics**
builds flexible, resilient and scalable Layer 2 fabrics with TRILL together with HP IRF
- **NEW Multitenant Device Context (MDC)**
virtualizes a physical switch into multiple logical devices, with each logical switch having its own processes, configuration, and administration
- **Data Center Bridging (DCB) protocols**
supports IEEE 802.1Qaz Data Center Bridging Exchange (DCBX) and Enhanced Transmission Selection (ETS) and IEEE 802.1Qbb Priority Flow Control (PFC) for converged fabrics
- **Fibre Channel over Ethernet (FCoE) capabilities**
delivers support for FCoE, including expansion, fabric, trunk VF and N ports, and aggregation of E-port and N-port virtualization
- **Edge Virtual Bridging (EVB) with Virtual Ethernet Port Aggregator (VEPA) support**
provides connectivity into the virtualization-ready data center environment
- **Front-to-back airflow design**
accommodates deployment in data centers utilizing hot-cold aisles

Performance

- **High-performance fully-distributed architecture**
delivers up to 7.7 Tbps switching capacity and 5.76 Bpps throughput with non-blocking wire-speed performance and latency as low as 3 microseconds
- **High-density 1/10GbE and 40GbE interface connectivity**

Overview

offers up to eight interface module slots to scale up to 384 1GbE/10GbE and 64 40GbE ports

- **Scalable system design**
provides investment protection to support future technologies and higher-speed connectivity, as the switch is designed for increased backplane bandwidth

Product architecture

- **Advanced Comware modular operating system**
brings native high stability, independent process monitoring and restart through the modular design and multiple processes of HP Comware v7 software; supports enhanced serviceability functions
- **In-Service Software Upgrade (ISSU)**
provides an upgrade of the entire chassis, or an individual task or process, with zero packet loss
- **Distributed architecture with separation of data and control planes**
delivers enhanced fault tolerance and facilitates continuous operation and zero service disruption during planned or unplanned control-plane events

Resiliency and high availability

- **Intelligent Resilient Framework (IRF)**
creates virtual resilient switching fabrics, where two or more switches perform as a single L2 switch and L3 router; switches do not have to be co-located and can be part of a disaster-recovery system; servers or switches can be attached using standard LACP for automatic load balancing and high availability; can eliminate the need for complex protocols like Spanning Tree Protocol, Equal-Cost Multipath (ECMP), or VRRP, thereby simplifying network operation
- **Redundant/load-sharing fabrics, management, fan assemblies, and power supplies**
increases total performance and power available while providing hitless, stateful failover
- **Hot-swappable modules**
allows replacement of modules without any impact on other modules
- **Graceful restart**
allows routers to indicate to others their capability to maintain a routing table during a temporary shutdown and significantly reduces convergence times upon recovery; supports OSPF, BGP, and IS-IS
- **Virtual Router Redundancy Protocol (VRRP)**
allows groups of two routers to dynamically back each other up to create highly available routed environments
- **Device Link Detection Protocol (DLDP)**
monitors link connectivity and shuts down ports at both ends if unidirectional traffic is detected, preventing loops in STP-based networks
- **Hitless patch upgrades**
allows patches and new service features to be installed without restarting the equipment, increasing network uptime and facilitating maintenance
- **IEEE 802.3ad Link Aggregation Control Protocol (LACP)**
supports up to 1024 trunk groups and up to 16 members per trunk; supports static or dynamic groups and a user-selectable hashing algorithm
- **Passive design system**
delivers increased system reliability as backplane has no active components
- **Ultrafast protocol convergence (subsecond) with standard-based failure detection—Bidirectional Forwarding Detection (BFD)**
enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and IRF

Layer 2 switching

- **VLAN**
supports up to 4,094 port-based or IEEE 802.1Q-based VLANs; also supports MAC-based VLANs, protocol-based VLANs, and IP-subnet-based VLANs for added flexibility
- **Bridge Protocol Data Unit (BPDU) tunneling**

Overview

transmits Spanning Tree Protocol BPDUs transparently, allowing correct tree calculations across service providers, WANs, or MANs

- **Port mirroring**
duplicates port traffic (ingress and egress) to a local or remote monitoring port; supports four mirroring groups, with an unlimited number of ports per group
- **Spanning Tree Protocol (STP)**
supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- **Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) protocol snooping**
controls and manages the flooding of multicast packets in a Layer 2 network
- **IEEE 802.1ad QinQ and selective QinQ**
increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network
- **Per-VLAN Spanning Tree Plus (PVST+)**
allows each VLAN to build a separate spanning tree to improve link bandwidth usage in network environments with multiple VLANs
- **Isolation at data link layer with private VLANs**
provides, through a two-tier VLAN structure, an additional layer of protection, simplifying network configuration while saving VLAN resources

Layer 3 routing

- **Open shortest path first (OSPF)**
delivers faster convergence; uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Intermediate system to intermediate system (IS-IS)**
uses a path vector Interior Gateway Protocol (IGP), which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Border Gateway Protocol 4 (BGP-4)**
delivers an implementation of the Exterior Gateway Protocol (EGP) utilizing path vectors; uses TCP for enhanced reliability for the route discovery process; reduces bandwidth consumption by advertising only incremental updates; supports extensive policies for increased flexibility; scales to very large networks
- **Multiprotocol Label Switching (MPLS)**
uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, which reduces complexity and increases performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- **Dual IP stack**
maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- **Equal-Cost Multipath (ECMP)**
enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth
- **Policy-based routing**
makes routing decisions based on policies set by the network administrator
- **Static IPv4 routing**
provides simple manually configured IPv4 routing
- **Routing Information Protocol (RIP)**
uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **IP performance optimization**
provides a set of tools to improve the performance of IPv4 networks; includes directed broadcasts, customization of TCP parameters, support of ICMP error packets, and extensive display capabilities
- **Unicast Reverse Path Forwarding (uRPF)**
limits erroneous or malicious traffic in accordance with RFC 3074
- **Static IPv6 routing**

Overview

provides simple, manually configured IPv6 routing Routing Information Protocol next generation (RIPng) extends RIPv2 to support IPv6 addressing

- **OSPFv3**
provides OSPF support for IPv6
- **IS-IS for IPv6**
extends IS-IS to support IPv6 addressing
- **BGP+**
extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **Multiprotocol Label Switching (MPLS) Layer 3 VPN**
allows Layer 3 VPNs across a provider network; uses MP-BGP to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility
- **Multiprotocol Label Switching (MPLS) Layer 2 VPN**
establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies
- **Virtual Private LAN Service (VPLS)**
establishes point-to-multipoint Layer 2 VPNs across a provider network
- **IPv6 tunneling**
provides an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels, and IPv6 on VPN to Provider Edge (6VPE) router tunnel

Quality of Service (QoS)

- **IEEE 802.1p prioritization**
delivers data to devices based on the priority and type of traffic
- **Flexible classification**
creates traffic classes based on access control lists (ACLs), IEEE 802.1p precedence, IP, and DSCP or Type of Service (ToS) precedence; supports filter, redirect, mirror, remark, and logging
- **Bandwidth shaping**
 - **Port-based rate limiting**
provides per-port ingress-/egress-enforced increased bandwidth
 - **Classifier-based rate limiting**
uses an access control list (ACL) to enforce increased bandwidth for ingress traffic on each port
 - **Reduced bandwidth**
provides per-port, per-queue egress-based reduced bandwidth
- **Broad QoS feature set**
provides support for Strict Priority Queuing (SP), Weighted Fair Queuing (WFQ), Weighted Deficit Round Robin(WDRR), SP+WDRR together, configurable buffers, Explicit Congestion Notification (ECN), and Weighted Random Early Detection (WRED)
- **Traffic policing**
supports Committed Access Rate (CAR) and line rate

Layer 3 services

- **Address Resolution Protocol (ARP)**
determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper**
redirects UDP broadcasts to specific IP subnets to prevent server spoofing

Overview

- **Dynamic Host Configuration Protocol (DHCP)**
simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Management

- **Management interface control**
enables or disables each of the following interfaces depending on security preferences: console port, telnet port, or reset button
- **Industry-standard CLI with a hierarchical structure**
reduces training time and expenses, and increases productivity in multivendor installations
- **SNMPv1, v2, and v3**
provide complete support of SNMP; provide full support of industry-standard Management Information Base (MIB) plus private extensions; SNMPv3 supports increased security using encryption
- **sFlow (RFC 3176)**
provides scalable ASIC-based wirespeed network monitoring and accounting with no impact on network performance; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Remote monitoring (RMON)**
uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group
- **Debug and sampler utility**
supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP)**
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Network Quality Analyzer (NQA)**
analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays and file transfer rates; allows a network manager to determine overall network performance and to diagnose and locate network congestion points or failures
- **Information center**
provides a central information center for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- **IEEE 802.1AB Link Layer Discovery Protocol (LLDP)**
advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

Connectivity

- **Jumbo frames**
allows high-performance backups and disaster-recovery systems with a maximum frame size of 9k bytes
- **Loopback**
supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **Ethernet operations, administration and maintenance (OAM)**
detects data link layer problems that occurred in the "last mile" using the IEEE 802.3ah OAM standard; monitors the status of the link between two devices
- **Monitor link**
collects statistics on performance and errors on physical links, increasing system availability
- **Packet storm protection**
protects against unknown broadcast, unknown multicast, or unicast storms with user-defined thresholds
- **Flow control**

Overview

provides back pressure using standard IEEE 802.3x, reducing congestion in heavy traffic situations

Security

- **Access control list (ACL)**
supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent unauthorized users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **Remote Authentication Dial-In User Service (RADIUS)**
eases switch security access administration by using a password authentication server
- **Terminal Access Controller Access-Control System (TACACS+)**
delivers an authentication tool using TCP with encryption of the full authentication request, providing additional security
- **Secure shell (SSHv2)**
uses external servers to securely log in to a remote device; with authentication and encryption, it protects against IP spoofing and plain-text password interception; increases the security of Secure FTP (SFTP) transfers
- **DHCP snooping**
helps ensure that DHCP clients receive IP addresses from authorized DHCP servers and maintain a list of DHCP entries for trusted ports; prevents reception of fake IP addresses and reduces ARP attacks, improving security
- **IP Source Guard**
filters packets on a per-port basis, which prevents illegal packets from being forwarded
- **ARP attack protection**
protects against attacks that use a large number of ARP requests, using a host-specific, user-selectable threshold
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **IEEE 802.1X support**
provides port-based user authentication with support for Extensible Authentication Protocol (EAP) MD5, TLS, TTLS, and PEAP with choice of AES, TKIP, and static or dynamic WEP encryption for protecting wireless traffic between authenticated clients and the access point
- **Multiple user authentication methods**
 - **IEEE 802.1X**
uses an IEEE 802.1X supplicant on the client in conjunction with a RADIUS server to authenticate in accordance with industry standards
 - **Web-based authentication**
provides a browser-based environment, similar to IEEE 802.1X, to authenticate clients that do not support the IEEE 802.1X supplicant
 - **MAC-based authentication**
authenticates the client with the RADIUS server based on the client's MAC address

Multicast support

- **Internet Group Management Protocol (IGMP)**
utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3
- **Protocol Independent Multicast (PIM)**
defines modes of Internet IPv4 and IPv6 multicasting to allow one-to-many and many-to-many transmission of information; PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Mode (SSM) are supported
- **Multicast Source Discovery Protocol (MSDP)**
allows multiple PIM-SM domains to interoperate; is used for inter-domain multicast applications
- **Multicast Border Gateway Protocol (MBGP)**
allows multicast traffic to be forwarded across BGP networks separately from unicast traffic

Integration

Overview

- **VPN 20Gbps 11900 Firewall Module**
provides enhanced stateful packet inspection and filtering; supports flexible security zones and virtual firewall containment; delivers advanced VPN services with 3DES and AES encryption at high performance and low latency; offers Web content filtering and application prioritization and optimization

Warranty and support

- **1-year warranty**
advance hardware replacement with 10-calendar-day delivery (available in most countries)
- **Electronic and telephone support**
limited electronic and business-hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

HP FF 11908-V Switch Chassis

JG608A

- Must select min 1 Interface Module
- Must select min 4 Fabric Modules
- Must select min 1 Management Module
- Must select min 1 Power Supply
- 20U - Height

Internal Power Supplies

System (std 0 // max 6) User Selection (min 1 // max 6) per switch enclosure

HP FF 11900 2500W AC Power Supply

JG616A

- includes 1 x c19, 2500w

See Configuration
Note:1, 2, 3

NOTE: 11900 provides 5+1 Redundancy. Select an appropriate number of power supplies based on the maximum output power of your system and redundancy requirements. For component power consumption consult the install guide.

PDU Cable NA/MEX/TW/JP

JG616A#B2B

- " C19 PDU Jumper Cord (NA/MEX/TW/JP)

PDU Cable ROW

JG616A#B2C

- C19 PDU Jumper Cord (ROW)

High Volt Switch to Wall Power Cord

JG616A#B2E

- NEMA L6-20P Cord

HP FF 11900 2400W DC Power Supply

JG617A

- NEMA L6-20P Cord

See Configuration
Note:1, 6

Configuration Rules

Note 1 If more than 1 power supply is selected they, must all be the same Sku number.

Note 2 Localization required on orders without #B2B, #B2C or #B2E options.

Note 3 #B2E is Offered only in NA, Mexico, Taiwan and Japan.

Note 6 One of these cables is required when ordering this power supply: (Use #B01 if switch is CTO) - if applicable
HP 10500 -48V 3m DC Power Supply Cable

JG390A

Configuration

HP 10500 -48V 15m DC Power Supply Cable

JG391A

Remarks: Drop down under power supply should offer the following options and results:
 Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
 Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)
 High Volt Switch/Router/Power Supply to Wall Power Cord - #B2E Option. (Offered only in North America, Mexico, Taiwan, and Japan)

Modules

Interface Modules

System (std 0 // max 8) User Selection (min 1 // max 8) per enclosure

HP FF 11900 24p 1/10GBASE-T SF Mod

JG615A

- No Transceivers

HP FF 11900 32p 10GbE SFP+ SF Mod

JG611A

- min=0 \ max=32 SFP+ Transceivers

See Configuration Note:1, 2, 4

HP FF 11900 48p 10GbE SFP+ SF Mod

JG612A

- min=0 \ max=48 SFP+ Transceivers

See Configuration Note:1, 2

HP FF 11900 4p 40GbE QSFP+ SF Mod

JG613A

- min=0 \ max=4 QSFP+ Transceivers

See Configuration Note:3

HP FF 11900 8p 40GbE QSFP+ SF Mod

JG614A

- min=0 \ max=8 QSFP+ Transceivers

See Configuration Note:3

HP FF 11900 2p 100GbE CFP SE Mod

JG918A

- min=0 \ max=2 CFP Transceivers

See Configuration Note:8

HP 10500/11900/7500 20Gbps VPN FW Mod

JG372A

- min=0 \ max=2 SFP Transceivers

See Configuration Note:5

HP 10500/7500 20G Unified Wired-WLAN Mod

JG639A

- No supported Transceivers

See Configuration Note:7

Configuration Rules

Configuration

Note 1	The following Transceivers install into this Module:	
	HP X170 1G SFP LC LH70 1550 Transceiver	JD109A
	HP X170 1G SFP LC LH70 1570 Transceiver	JD110A
	HP X170 1G SFP LC LH70 1590 Transceiver	JD111A
	HP X170 1G SFP LC LH70 1610 Transceiver	JD112A
	HP X170 1G SFP LC LH70 1470 Transceiver	JD113A
	HP X170 1G SFP LC LH70 1490 Transceiver	JD114A
	HP X170 1G SFP LC LH70 1510 Transceiver	JD115A
	HP X170 1G SFP LC LH70 1530 Transceiver	JD116A
	HP X120 1G SFP LC LH100 Transceiver	JD103A
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X120 1G SFP RJ45 T Transceiver	JD089B
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP LC BX 10-U Transceiver	JD098B
	HP X120 1G SFP LC BX 10-D Transceiver	JD099B
Note 2	The following Transceivers install into this Module:	
	HP X130 10G SFP+ LC SR Transceiver	JD092B
	HP X130 10G SFP+ LC LR Transceiver	JD094B
	HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
	HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
	HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
	HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
	HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
	HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
Note 3	The following 40G Transceivers install into this Module:	
	HP X140 40G QSFP+ LC LR4 SM 10km 1310nm Transceiver	JG661A
	HP X140 40G QSFP+ MPO SR4 Transceiver	JG325B
	HP X140 40G QSFP+ MPO MM 850nm CSR4 300m Transceiver	JG709A
	HP X240 40G QSFP+ QSFP+ 3m Direct Attach Copper Cable	JG327A
	HP X240 40G QSFP+ QSFP+ 5m Direct Attach Copper Cable	JG328A
	HP X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable	JG329A
	HP X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable	JG330A
	HP X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable	JG331A
Note 4	The following Transceivers install into this Module:	
	HP X130 10G SFP+ LC LRM Transceiver	JD093B
Note 5	The following Transceivers install into this Module:	
	HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
	HP X125 1G SFP LC LH70 Transceiver	JD063B
	HP X120 1G SFP LC SX Transceiver	JD118B
	HP X120 1G SFP LC LX Transceiver	JD119B

Configuration

Note 7 Maximum of this Module per Chassis:
JG608A min=0\max=7 per Chassis
There are no restrictions on which slots these modules may go in.

Note 8 The following Transceivers install into this Module:
HP X150 100G CFP LC LR4 10km SM Transceiver JG829A

Fabric Modules

System (std 0 // max 4) User Selection (min 4 // max 4) per enclosure

HP FF 11908 1.92Tbps Type D Fabric Mod JG610A

- No supported Transceivers

Management Modules

System (std 0 // max 2) User Selection (min 1 // max 2) per enclosure

HP FF 11900 Main Processing Unit JG609A

Remarks: These modules can only be inserted into Slots 4 and 5.

Transceivers

SFP Transceivers

HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X120 1G SFP LC LH40 1550nm XCVR	JD062A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X125 1G SFP LC LH40 1310nm XCVR	JD061A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X170 1G SFP LC LH70 1550 Transceiver	JD109A
HP X170 1G SFP LC LH70 1570 Transceiver	JD110A
HP X170 1G SFP LC LH70 1590 Transceiver	JD111A
HP X170 1G SFP LC LH70 1610 Transceiver	JD112A
HP X170 1G SFP LC LH70 1470 Transceiver	JD113A
HP X170 1G SFP LC LH70 1490 Transceiver	JD114A
HP X170 1G SFP LC LH70 1510 Transceiver	JD115A
HP X170 1G SFP LC LH70 1530 Transceiver	JD116A

SFP+ Transceivers

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B

Configuration

HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ SFP+ 0.65m DAC Cable	JD095C
HP X240 10G SFP+ SFP+ 1.2m DAC Cable	JD096C
HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C
HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C
HP X240 10G SFP+ 7m DAC Cable	JC784C

QSFP+ Transceivers

HP X140 40G QSFP+ LC LR4 SM XCVR	JG661A
HP X140 40G QSFP+ MPO SR4 XCVR	JG325B
HP X140 40G QSFP+ CSR4 300m XCVR	JG709A
HP X240 40G QSFP+ QSFP+ 1m Direct Attach Copper Cable	JG326A
HP X240 40G QSFP+ QSFP+ 3m Direct Attach Copper Cable	JG327A
HP X240 40G QSFP+ QSFP+ 5m Direct Attach Copper Cable	JG328A
HP X240 QSFP+ 4x10G SFP+ 1m Direct Attach Copper Cable	JG329A
HP X240 QSFP+ 4x10G SFP+ 3m Direct Attach Copper Cable	JG330A
HP X240 QSFP+ 4x10G SFP+ 5m Direct Attach Copper Cable	JG331A

CFP Transceivers

HP X150 100G CFP LC LR4 10km SM XCVR	JG829A
--------------------------------------	--------

Switch Enclosure Options

Mounting Kit

HP X421 Chassis Universal Rck Mntg Kit	JC665A See Configuration Note:1
--	--

Configuration Rules

Note 1 If any 11900 switch is installed into a rack, Then this Rack Mounting kit is required.

Remarks: Default a quantity of 1 when Switch is selected.

Software Licenses

HP Unified Wired-WLAN 128 AP E-LTU (min 0 // max 7) REMARK: This license is for use with the Primary Controllers.	JG649AAE See Configuration Note:1
---	--

HP Unified Wired-WLAN 128 AP Redundant E-LTU (min 0 // max 7) REMARK: This license is for use with the Redundant Controllers.	JG902AAE See Configuration Note:1
---	--

Configuration Rules

Note 1 Only supported on JG639A and JG645A.

Configuration

Remarks: JG649AAE is optional to increase the AP by a count of 128 per E-LTU
JG902AAE - Redundant access point licenses are intended for use only on a redundant controller module in a 1+1 or N+1 configuration or when extra access point capacity is required for failover in an N+N configuration.

Fans

HP FF 11908-V Spare Fan Assy	JG618A
------------------------------	--------

Power Supply Cables

(std 0 // max 1) User Selection (min 1 // max 1) per DC Power Supply

HP 10500 -48V 3m DC Power Supply Cable	JG390A
HP 10500 -48V 15m DC Power Supply Cable	JG391A

Technical Specifications

HP FlexFabric 11908-V Switch Chassis (JG608A)

I/O ports and slots	8 I/O module slots Supports a maximum of 384 1/10GbE ports or 192 1/10GBASE-T ports or 64 40GbE ports, or a combination	
Additional ports and slots	2 MPU (for management modules) slots 4 switch fabric slots	
Power supplies	6 power supply slots 1 minimum power supply required (ordered separately)	
Fan tray	includes: 1 x JC634A 1 fan tray slot	
Physical characteristics	Dimensions	17.32(w) x 25.98(d) x 34.88(h) in (43.99 x 65.99 x 88.6 cm) (20U height)
	Weight	169.53 lb (76.9 kg) chassis
	Full configuration weight	331.31 lb (150.28 kg)
Memory and processor	Management module	Dual Core MIPS64 @ 1.2 GHz, 512 MB flash, 8 GB DDR2 SDRAM
Mounting	Mounts in an EIA-standard 19 in. rack or other equipment cabinet (hardware included); horizontal surface mounting only	
Performance	Throughput	up to 5.8 Bpps (64-byte packets)
	Switching capacity	7.7 Tbps
	Routing table size	16384 entries (IPv4), 8192 entries (IPv6)
	MAC address table size	131072 entries
	Reliability	Availability
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
	Altitude	up to 13,123 ft (4 km)
	Acoustic	Low-speed fan: 61.6 dB, High-speed fan: 72.6 dB
Electrical characteristics	AC Voltage	100-120/200-240 VAC, depending on configuration
	DC Voltage	-48 to -60 VDC, depending on configuration
	Current	16/60 A
	Power output	2500 W
	Frequency	50/60 Hz
	Notes	Based on a common power supply of 2,500 W (AC)
	Safety	CAN/CSA 22.2 No. 60950-1; FCC Part 15, Subpart B; FDA 21 CFR Subchapter J; ROHS Compliance; IEC 60950-1 :Second Edition ; EN 60950-1:2006 + A11:2009; AS/NZS 60950-1; IEC 60825-1; UL 60950-1, 2nd Edition; EN60825-2:2004+A1:2007
Emissions	VCCI Class A; EN 55022 Class A; CISPR 22 Class A; IEC/EN 61000-3-2; IEC/EN 61000-3-3; ICES-003 Class A; AS/NZS CISPR 22 Class A; FCC (CFR 47, Part 15) Class A; GB9254	
Immunity	Generic	Directive 2004/108/EC
	EN	EN 55024:1998+ A1:2001 + A2:2003; ETSI EN 300 386 V1.3.3
	ESD	EN 61000-4-2
	Radiated	EN 61000-4-3
	EFT/Burst	EN 61000-4-4

Technical Specifications

Surge	EN 61000-4-5
Conducted	EN 61000-4-6
Power frequency magnetic field	IEC 61000-4-8
Voltage dips and interruptions	EN 61000-4-11
Harmonics	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3

Management

IMC - Intelligent Management Center; command-line interface; out-of-band management (serial RS-232C); SNMP Manager; Telnet; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP	RFC 3315 DHCPv6 (client and relay)
RFC 1771 BGPv4	RFC 3484 Default Address Selection for IPv6
RFC 1772 Application of the BGP	RFC 3513 IPv6 Addressing Architecture
RFC 1997 BGP Communities Attribute	RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6
RFC 1998 PPP Gandalf FZA Compression Protocol	RFC 3810 MLDv2 for IPv6
RFC 2385 BGP Session Protection via TCP MD5	RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)
RFC 2439 BGP Route Flap Damping	RFC 4861 IPv6 Neighbor Discovery
RFC 2796 BGP Route Reflection	RFC 4862 IPv6 Stateless Address Auto-configuration
RFC 2858 BGP-4 Multi-Protocol Extensions	
RFC 2918 Route Refresh Capability	
RFC 3065 Autonomous System Confederations for BGP	
RFC 3392 Capabilities Advertisement with BGP-4	MIBs
RFC 4271 A Border Gateway Protocol 4 (BGP-4)	RFC 1156 (TCP/IP MIB)
RFC 4272 BGP Security Vulnerabilities Analysis	RFC 1157 A Simple Network Management Protocol (SNMP)
RFC 4273 Definitions of Managed Objects for BGP-4	RFC 1215 A Convention for Defining Traps for use with the SNMP
RFC 4274 BGP-4 Protocol Analysis	RFC 1229 Interface MIB Extensions
RFC 4275 BGP-4 MIB Implementation Survey	RFC 1493 Bridge MIB
RFC 4276 BGP-4 Implementation Report	RFC 1573 SNMP MIB II
RFC 4277 Experience with the BGP-4 Protocol	RFC 1643 Ethernet MIB
RFC 4360 BGP Extended Communities Attribute	RFC 1657 BGP-4 MIB
RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)	RFC 1724 RIPv2 MIB
RFC 5291 Outbound Route Filtering Capability for BGP-4	RFC 1907 SNMPv2 MIB
RFC 5292 Address-Prefix-Based Outbound Route Filter for BGP-4	RFC 2011 SNMPv2 MIB for IP
	RFC 2012 SNMPv2 MIB for TCP
	RFC 2013 SNMPv2 MIB for UDP
	RFC 2096 IP Forwarding Table MIB
Denial of service protection	RFC 2233 Interface MIB
Automatic filtering of well-known denial-of-service packets	RFC 2452 IPV6-TCP-MIB
CPU DoS Protection	RFC 2454 IPV6-UDP-MIB
Rate Limiting by ACLs	RFC 2465 IPV6 MIB
	RFC 2466 ICMPv6 MIB
Device management	RFC 2571 SNMP Framework MIB
RFC 1157 SNMPv1/v2c	RFC 2572 SNMP-MPD MIB
RFC 1305 NTPv3	RFC 2573 SNMP-Target MIB
RFC 1902 (SNMPv2)	RFC 2578 Structure of Management Information Version

Technical Specifications

RFC 2579 (SMIPv2 Text Conventions)
RFC 2580 (SMIPv2 Conformance)
RFC 2819 (RMON groups Alarm, Event, History and Statistics only)
HTTP, SSHv1, and Telnet
Multiple Configuration Files
Multiple Software Images
SSHv1/SSHv2 Secure Shell
TACACS/TACACS+
Web UI

General protocols

IEEE 802.1ad Q-in-Q
IEEE 802.1ag Service Layer OAM
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
IEEE 802.1X PAE
IEEE 802.3ab 1000BASE-T
IEEE 802.3ac (VLAN Tagging Extension)
IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3ae 10-Gigabit Ethernet
IEEE 802.3ah Ethernet in First Mile over Point to Point Fiber - EFMF
IEEE 802.3ba 40 and 100 Gigabit Ethernet Architecture
IEEE 802.3x Flow Control
IEEE 802.3z 1000BASE-X
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1027 Proxy ARP
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1213 Management Information Base for Network Management of TCP/IP-based internets
RFC 1293 Inverse Address Resolution Protocol
RFC 1305 NTPv3
RFC 1350 TFTP Protocol (revision 2)
RFC 1393 Traceroute Using an IP Option

2 (SMIPv2)
RFC 2580 Conformance Statements for SMIPv2
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2668 802.3 MAU MIB
RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 2787 VRRP MIB
RFC 2819 RMON MIB
RFC 2925 Ping MIB
RFC 2932IP (Multicast Routing MIB)
RFC 2933 IGMP MIB
RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 3414 SNMP-User based-SM MIB
RFC 3415 SNMP-View based-ACM MIB
RFC 3417 Simple Network Management Protocol (SNMP) over IEEE 802 Networks
RFC 3418 MIB for SNMPv3
RFC 3595 Textual Conventions for IPv6 Flow Label
RFC 3621 Power Ethernet MIB
RFC 3813 MPLS LSR MIB
RFC 3814 MPLS FTN MIB
RFC 3815 MPLS LDP MIB
RFC 3826 AES for SNMP's USM MIB
RFC 4133 Entity MIB (Version 3)
RFC 4444 Management Information Base for Intermediate System to Intermediate System (IS-IS)

MPLS

RFC 2205 Resource ReSerVation Protocol
RFC 2209 Resource ReSerVation Protocol (RSVP)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 3031 Multiprotocol Label Switching Architecture
RFC 3032 MPLS Label Stack Encoding
RFC 3107 Carrying Label Information in BGP-4
RFC 3212 Constraint-Based LSP Setup using LDP
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3487 Graceful Restart Mechanism for LDP
RFC 3564 Requirements for Support of Differentiated Service-aware MPLS Traffic Engineering
RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs)
RFC 4379 Detecting Multi-Protocol Label Switched (MPLS) Data Plane Failures
RFC 4447 Pseudowire Setup and Maintenance

Technical Specifications

RFC 1519 CIDR
RFC 1531 Dynamic Host Configuration Protocol
RFC 1533 DHCP Options and BOOTP Vendor Extensions
RFC 1591 DNS (client only)
RFC 1624 Incremental Internet Checksum
RFC 1701 Generic Routing Encapsulation
RFC 1721 RIP-2 Analysis
RFC 1723 RIP v2
RFC 1812 IPv4 Routing
RFC 2082 RIP-2 MD5 Authentication
RFC 2091 Trigger RIP
RFC 2131 DHCP
RFC 2138 Remote Authentication Dial In User Service (RADIUS)
RFC 2236 IGMP Snooping
RFC 2338 VRRP
RFC 2453 RIPv2
RFC 2644 Directed Broadcast Control
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2865 Remote Authentication Dial In User Service (RADIUS)
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3567 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication
RFC 3719 Recommendations for Interoperable Networks using Intermediate System to Intermediate System (IS-IS)
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3787 Recommendations for Interoperable IP Networks using Intermediate System to Intermediate System (IS-IS)
RFC 3847 Restart signaling for IS-IS
RFC 4251 The Secure Shell (SSH) Protocol Architecture
RFC 4486 Subcodes for BGP Cease Notification Message
RFC 4884 Extended ICMP to Support Multi-Part Messages
RFC 4941 Privacy Extensions for Stateless Address Autoconfiguration in IPv6
RFC 5130 A Policy Control Mechanism in IS-IS Using Administrative Tags

IP multicast

Using LDP
RFC 4448 Encapsulation Methods for Transport of Ethernet over MPLS Networks
RFC 4664 Framework for Layer 2 Virtual Private Networks
RFC 4665 Service Requirements for Layer 2 Provider Provisioned Virtual Private Networks
RFC 4761 Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling
RFC 4762 Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling
RFC 5036 LDP Specification

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
RFC 1155 Structure of Management Information
RFC 1157 SNMPv1
RFC 1448 Protocol Operations for version 2 of the Simple Network Management Protocol (SNMPv2)
RFC 2211 Controlled-Load Network
RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
RFC 3176 sFlow
RFC 3411 SNMP Management Frameworks
RFC 3412 SNMPv3 Message Processing
RFC 3414 SNMPv3 User-based Security Model (USM)
RFC 3415 SNMPv3 View-based Access Control Model (VACM)
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with OSPF
RFC 1765 OSPF Database Overflow
RFC 1850 OSPFv2 Management Information Base (MIB), traps
RFC 2154 OSPF w/ Digital Signatures (Password, MD-5)
RFC 2328 OSPFv2
RFC 2370 OSPF Opaque LSA Option
RFC 3101 OSPF NSSA
RFC 3137 OSPF Stub Router Advertisement
RFC 3623 Graceful OSPF Restart
RFC 3630 Traffic Engineering Extensions to OSPFv2
RFC 4061 Benchmarking Basic OSPF Single Router Control Plane Convergence
RFC 4062 OSPF Benchmarking Terminology and Concepts
RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks

Technical Specifications

RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 3376 IGMPv3
RFC 3446 Anycast Rendezvous Point (RP) mechanism using Protocol Independent Multicast (PIM) and Multicast Source Discovery Protocol (MSDP)
RFC 3618 Multicast Source Discovery Protocol (MSDP)
RFC 3973 PIM Dense Mode
RFC 4541 Considerations for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD) Snooping Switches
RFC 4601 PIM Sparse Mode
RFC 4604 Using Internet Group Management Protocol Version 3 (IGMPv3) and Multicast Listener Discovery Protocol Version 2 (MLDv2) for Source-Specific Multicast
RFC 4605 IGMP/MLD Proxying
RFC 4607 Source-Specific Multicast for IP
RFC 5059 Bootstrap Router (BSR) Mechanism for Protocol Independent Multicast (PIM)

IPv6

RFC 1886 DNS Extension for IPv6
RFC 1887 IPv6 Unicast Address Allocation Architecture
RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2081 RIPng Protocol Applicability Statement
RFC 2292 Advanced Sockets API for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2375 IPv6 Multicast Address Assignments
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 2473 Generic Packet Tunneling in IPv6
RFC 2526 Reserved IPv6 Subnet Anycast Addresses
RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 2545 Use of MP-BGP-4 for IPv6
RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 2740 OSPFv3 for IPv6
RFC 2767 Dual stacks IPv4 & IPv6

RFC 4222 Prioritized Treatment of Specific OSPF Version
2 Packets and Congestion Avoidance
RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)
RFC 4811 OSPF Out-of-Band LSDB Resynchronization
RFC 4812 OSPF Restart Signaling
RFC 4813 OSPF Link-Local Signaling
RFC 4940 IANA Considerations for OSPF

QoS/CoS

IEEE 802.1P (CoS)
RFC 1349 Type of Service in the Internet Protocol Suite
RFC 2211 Specification of the Controlled-Load Network Element Service
RFC 2212 Guaranteed Quality of Service
RFC 2474 DSCP DiffServ
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 1334 PPP Authentication Protocols (PAP)
RFC 1492 TACACS+
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP)
RFC 2409 The Internet Key Exchange (IKE)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 2868 RADIUS Attributes for Tunnel Protocol Support
RFC 2869 RADIUS Extensions
Access Control Lists (ACLs)
Guest VLAN for 802.1x
MAC Authentication
Port Security
SSHv1/SSHv2 Secure Shell

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm

Technical Specifications

RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 3307 IPv6 Multicast Address Allocation

RFC 2407 - Domain of interpretation
RFC 2547 BGP/MPLS VPNs
RFC 2917 A Core MPLS IP VPN Architecture
RFC 4302 - IP Authentication Header (AH)
RFC 4303 - IP Encapsulating Security Payload (ESP)

Accessories

HP FlexFabric 11900 Switch Series accessories

Modules

HP FlexFabric 11900 48-port 10GbE SFP+ SF Module	JG612A
HP FlexFabric 11900 32-port 10GbE SFP+ SF Module	JG611A
HP FlexFabric 11900 Main Processing Unit	JG609A
HP FlexFabric 11900 24-port 1/10GBASE-T SF Module	JG615A
HP FlexFabric 11900 4-port 40GbE QSFP+ SF Module	JG613A
HP FlexFabric 11900 8-port 40GbE QSFP+ SF Module	JG614A
NEW HP FlexFabric 11900 2-port 100GbE CFP SE Module	JG918A

Transceivers

HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC LH100 Transceiver	JD103A
HP X120 1G SFP LC BX 10-D Transceiver	JD099B
HP X120 1G SFP LC BX 10-U Transceiver	JD098B
HP X170 1G SFP LC LH70 1470 Transceiver	JD113A
HP X170 1G SFP LC LH70 1490 Transceiver	JD114A
HP X170 1G SFP LC LH70 1510 Transceiver	JD115A
HP X170 1G SFP LC LH70 1530 Transceiver	JD116A
HP X170 1G SFP LC LH70 1550 Transceiver	JD109A
HP X170 1G SFP LC LH70 1570 Transceiver	JD110A
HP X170 1G SFP LC LH70 1590 Transceiver	JD111A
HP X170 1G SFP LC LH70 1610 Transceiver	JD112A
HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
HP X240 10G SFP+ SFP+ 7m Direct Attach Copper Cable	JC784C
HP X240 40G QSFP+ QSFP+ 1m Direct Attach Copper Cable	JG326A
HP X240 40G QSFP+ QSFP+ 3m Direct Attach Copper Cable	JG327A
HP X240 40G QSFP+ QSFP+ 5m Direct Attach Copper Cable	JG328A
HP X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable	JG329A
HP X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable	JG330A
HP X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable	JG331A
HP X140 40G QSFP+ MPO SR4 Transceiver	JG325B
HP X140 40G QSFP+ MPO MM 850nm CSR4 300m Transceiver	JG709A
HP X150 100G CFP LC LR4 10km SM Transceiver	JG829A
HP X150 100G CXP MPO SR 100m Multimode Transceiver	JG881A
HP X2A0 100G CXP CXP 10m Active Optical Cable	JG882A

Accessories

HP X2A0 100G CXP CXP 30m Active Optical Cable JG883A

Power Supply

[HP FlexFabric 11900 2500W AC Power Supply](#) JG616A

[HP FlexFabric 11900 2400W DC Power Supply](#) JG617A

Mounting Kit

HP X421 Chassis Universal 4-post Rack Mounting Kit JC665A

Power cords

HP 10500 -48V 3m DC Power Supply Cable JG390A

HP 10500 -48V 15m DC Power Supply Cable JG391A

Appliance

HP 10500/11900/7500 20Gbps VPN Firewall Module JG372A

HP FlexFabric 11908-V Switch Chassis (JG608A)

[HP FlexFabric 11908 1.92Tbps Type D Fabric Module](#) JG610A

[HP FlexFabric 11908-V Spare Fan Assembly](#) JG618A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

Modules

HP FlexFabric 11900 Main Processing Unit (JG609A) Physical characteristics	Dimensions	15.71(w) x 13.86(d) x 1.57(h) in (39.9 x 35.2 x 3.99 cm)
	Weight	6.55 lb (2.97 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP FlexFabric 11900 32-port 10GbE SFP+ SF Module (JG611A)	Ports	32 SFP+ 1/10GbE ports
	Physical characteristics	Dimensions 15.71(w) x 13.86(d) x 1.57(h) in (39.9 x 35.2 x 3.99 cm)
	Weight	7.61 lb (3.45 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP FlexFabric 11900 48-port 10GbE SFP+ SF Module (JG612A)	Ports	48 SFP+ 1/10GbE ports
	Physical characteristics	Dimensions 15.71(w) x 13.86(d) x 1.57(h) in (39.9 x 35.2 x 3.99 cm)
	Weight	9.1 lb (4.13 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP FlexFabric 11900 4-port 40GbE QSFP+ SF Module (JG613A)	Ports	4 QSFP+ 40-GbE ports
	Physical characteristics	Dimensions 15.71(w) x 13.86(d) x 1.57(h) in (39.9 x 35.2 x 3.99 cm)
	Weight	6.92 lb (3.14 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP FlexFabric 11900 8-port 40GbE QSFP+ SF Module (JG614A)	Ports	8 QSFP+ 40-GbE ports
	Physical characteristics	Dimensions 15.71(w) x 13.86(d) x 1.57(h) in (39.9 x 35.2 x 3.99 cm)
	Weight	7.43 lb (3.37 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Transceivers

HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)	Ports	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)	
	Connectivity	Connector type	LC
		Wavelength	1310 nm

Accessory Product Details

<p>A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.</p>	Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Electrical characteristics	Full configuration weight	0.04 lb. (0.02 kg)
		Power consumption typical	0.8 W
	Cabling	Power consumption maximum	1.0 W
		Cable type:	Single-mode fiber optic, complying with ITU-T G.652;
Services	Fiber type	Single Mode	
		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

<p>HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)</p> <p>A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.</p>	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)		
	Connectivity	Connector type	LC	
	Physical characteristics	Wavelength	1550 nm	
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Electrical characteristics	Full configuration weight	0.04 lb. (0.02 kg)	
Power consumption typical		0.8 W		
Cabling	Power consumption maximum	1.0 W		
	Cable type:	Single-mode fiber optic, complying with ITU-T G.652;		
Services	Fiber type	Single Mode		
		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

<p>HP X125 1G SFP LC LH70 Transceiver (JD063B)</p> <p>A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode</p>	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)		
	Connectivity	Connector type	LC	
	Physical characteristics	Wavelength	1550 nm	
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Electrical characteristics	Full configuration weight	0.04 lb. (0.02 kg)	
Power consumption typical		0.8 W		

Accessory Product Details

fiber.		Power consumption maximum	1.0 W
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
		Maximum distance: • 70km	
	Services	Fiber type	Single Mode
		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP X125 1G SFP RJ45 T Transceiver (JD089B) A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.	Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)		
	Connectivity	Connector type	RJ-45	
	Physical characteristics	Dimensions	2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)	
	Electrical characteristics	Full configuration weight	0.07 lb. (0.03 kg)	
	Cabling	Power consumption typical	0.8 W	
		Power consumption maximum	1.0 W	
	Services	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Ω differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;		
		Maximum distance: • 100m		
	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

HP X120 1G SFP LC BX 10-U Transceiver (JD098B) A small form-factor pluggable (SFP) Gigabit LX-BX10-U transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.	Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-U); Duplex: full only		
	Connectivity	Connector type	LC	
	Physical characteristics	Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Electrical characteristics	Full configuration weight	0.04 lb. (0.02 kg)	
		Power consumption typical	0.8 W	
		Power consumption maximum	1.0 W	
	Cabling	Maximum distance: • 10km		
		Fiber type	Single Mode	
Notes	TX 1310nm RX 1490nm			
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

HP X120 1G SFP LC BX 10- Ports	1 LC 1000BASE-BX10 port (IEEE 802.3ah Type 1000BASE-BX10-D); Duplex:
---------------------------------------	--

Accessory Product Details

D Transceiver (JD099B)

A small form-factor pluggable (SFP) Gigabit LX-BX10-D transceiver that provides a full duplex Gigabit solution up to 10km on a single mode cable.

Connectivity	full only	Connector type	LC
Physical characteristics	Dimensions		2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight		0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical		0.8 W
	Power consumption maximum		1.0 W
Cabling	Maximum distance: • Up to 10km	Fiber type	Single Mode
Notes	TX 1490nm RX 1310nm		
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

HP X120 1G SFP LC LH100 Transceiver (JD103A)

A small form factor pluggable (SFP) Gigabit LH100 transceiver that provides a full-duplex Gigabit solution up to 100km on a single mode fiber.

Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)		
Connectivity	Connector type		LC
	Wavelength		1550 nm
Electrical characteristics	Power consumption typical		0.8 W
	Power consumption maximum		1.0 W
Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	Maximum distance: • Up to 100km	Fiber type Single Mode
Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

HP X120 1G SFP LC SX Transceiver (JD118B)

A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.

Ports	1 LC 1000BASE-SX port		
Connectivity	Connector type		LC
	Wavelength		850 nm
Physical characteristics	Dimensions		2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
	Full configuration weight		0.04 lb. (0.02 kg)
Electrical characteristics	Power consumption typical		0.8 W
	Power consumption maximum		1.0 W
Cabling	Maximum distance: • FDDI Grade distance = 220m • OM1 = 275m		

Accessory Product Details

		<ul style="list-style-type: none"> • OM2 = 500m • OM3 = Not Specified by standard
		Cable length up to 550m
		Fiber type Multi Mode
Services		Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC LX Transceiver (JD119B) A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF	Ports	1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)
	Connectivity	Connector type LC Wavelength 1300 nm
	Physical characteristics	Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm) Full configuration weight 0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical 0.8 W Power consumption maximum 1.0 W
	Cabling	Cable type: Either single mode or multimode;
		Maximum distance: <ul style="list-style-type: none"> • 550m for Multimode • 10km for Singlemode
		Fiber type Both
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 7502 Fabric Module (JD196A)	Ports	1 RJ-45 dual-personality port; One console port, used for local or remote configuration and management 1 RJ-45 autosensing 10/100 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 1 Compact Flash port
	Physical characteristics	Dimensions 7.83(w) x 13.98(d) x 1.77(h) in (19.9 x 35.5 x 4.5 cm) Weight 2.98 lb. (1.35 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Power Supplies

HP FlexFabric 11900 2500W AC Power Supply (JG616A)	Physical characteristics	Dimensions 1.61(w) x 16.14(d) x 4.02(h) in (4.1 x 41.0 x 10.21 cm) Weight 9.26 lb (4.2 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about

Accessory Product Details

services and response times in your area, please contact your local HP sales office.

HP FlexFabric 11900 2400W DC Power Supply (JG617A)	Physical characteristics	Dimensions	1.61(w) x 16.14(d) x 4.02(h) in (4.1 x 41.0 x 10.2 cm)
		Weight	5.29 lb (2.4 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP FlexFabric 11908-V Switch Chassis (JG608A)

HP FlexFabric 11908 1.92Tbps Type D Fabric Module (JG610A)	Physical characteristics	Dimensions	16.77(w) x 11.73(d) x 1.57(h) in (42.6 x 29.79 x 3.99 cm)
		Weight	9.7 lb (4.4 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP FlexFabric 11908-V Spare Fan Assembly (JG618A)	Physical characteristics	Dimensions	17.32(w) x 25.75(d) x 3.15(h) in (43.99 x 65.41 x 8.0 cm)
		Weight	8.29 lb (3.76 kg)
	Services	Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Summary of Changes

Date	Version History	Action	Description of Change:
12-Dec-2014	From Version 9 to 10	Removed	Deleted SKU JG325A
18-Aug-2014	From Version 8 to 9	Added	New accessory: JG918A
		Changed	Product overview updated Configuration menu updated Technical Specifications updated
02-Jul-2014	From Version 7 to 8	Changed	Minor change on Overview section.
10-Jun-2014	From Version 6 to 7	Added	Added a new accessory: JG372A
31-Mar-2014	From Version 4 to 6	Changed	Transceivers were revised.
14-Oct-2014	From Version 3 to 4	Added	Added a new Transceiver in two locations in the Configuration section.
30-Sept-2014	From Version 2 to 3	Added	HP 10500/11900/7500 20Gbps VPN FW Mod was added to Modules.
12-Jul-2014	From Version 1 to 2	Changed	Made minor changes to the Configuration section.

Summary of Changes

To learn more, visit: www.hp.com/networking

© Copyright 2011-2014 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

4AA4-6972ENW, Created June 2013; Updated September 2013, Rev. 1