

Overview

HP 5820 Switch Series

Models

HP 5820X-14XG-SFP+ Switch with 2 Interface Slots & 1 OAA Slot	JC106B
HP 5820X-24XG-SFP+ Switch	JC102B
HP 5820AF-24XG Switch	JG219B

Key features

- For enterprise edge, or distribution/data center
- Up to 24 ports of 10GbE per unit/194 per stack
- Flex chassis—modular resiliency
- Cut-through switching for very low latency
- Hot-swappable I/O, power supplies, and fans

Product overview

The HP 5820 Switch Series supports advanced features that deliver a unique combination of unmatched 10 Gigabit Ethernet; high-availability architecture; full Layer 2/3 dual-stack IPv4/IPv6; and line-rate, low-latency performance on all ports. Extensible embedded application capabilities enable these switches to integrate services into the network, consolidating devices and appliances to simplify deployment and reduce power consumption and rack space. Extremely versatile, the switches can be used in high-performance, high-density building or department cores as part of a consolidated network; for data center top-of-rack server access; or as high-performance Layer 3, 10GbE aggregation switches in campus and data center networks.

Features and benefits

Quality of Service (QoS)

- **Powerful QoS feature**
creates traffic classes based on access control lists (ACLs), IEEE 802.1p precedence, IP, and DSCP or Type of Service (ToS) precedence; supports filter, redirect, mirror, or remark; supports the following congestion actions: strict priority (SP) queuing, weighted round robin (WRR), weighted fair queuing (WFQ), weighted random early discard (WRED), weighted deficit round robin (WDRR), and SP+WDRR
- **Integrated network services**
with support for open application architecture (OAA) modules, extends and integrates application capability into the network
- **Ring Resiliency Protection Protocol (RRPP)**
provides fast recovery for ring Ethernet-based topology; helps ensure consistent application performance for applications such as VoIP

Management

- **Remote configuration and management**
enables configuration and management through a secure Web browser or a CLI located on a remote device
- **IEEE 802.1ab LLDP discovery**
advertises and receives management information from adjacent devices on a network
- **USB support**
 - **File copy**
allows users to copy switch files to and from a USB flash drive
- **DHCP options**
provides server (RFC 2131), client, snooping, and relay options
- **SNMPv1, v2c, and v3**
facilitate centralized discovery, monitoring, and secure management of networking devices

Overview

- **sFlow**
provides scalable ASIC-based network monitoring and accounting; this allows network operators to gather a variety of sophisticated network statistics and information for capacity planning and real-time network monitoring purposes
- **Network Time Protocol (NTP)**
synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time

Connectivity

- **High-density port connectivity**
194 10GbE ports with a 40 Gbps resilient backplane
- **Auto-MDIX**
provides automatic adjustments for straight-through or crossover cables on all 10/100 and 10/100/1000 ports
- **Jumbo frames**
on Gigabit Ethernet and 10-Gigabit Ethernet ports, jumbo frames allow high-performance remote backup and disaster-recovery services
- **IPv6 native support**
 - **IPv6 host**
enables switches to be managed and deployed at the IPv6 network's edge
 - **Dual stack (IPv4/IPv6)**
transitions from IPv4 to IPv6, supporting connectivity for both protocols
 - **MLD snooping**
forwards IPv6 multicast traffic to the appropriate interface
 - **IPv6 ACL/QoS**
supports ACL and QoS for IPv6 network traffic, preventing traffic flooding
 - **IPv6 routing**
supports IPv6 static routes and IPv6 versions of RIP, OSPF, IS-IS, and Border Gateway Protocol (BGP) routing protocols

Performance

- **Hardware-based wire-speed access control lists (ACLs)**
helps provide high levels of security and ease of administration without impacting network performance with a feature-rich TCAM-based ACL implementation
- **Unique versatile architecture**
supports the best of both fixed-port and modular configurations
- **Cut-through switching**
delivers wire-speed, line-rate performance on all ports, as well as cut-through switching for low latency

Resiliency and high availability

- **Data center-optimized design**
the HP 5820AF-24XG Switch (JG219B) supports front-to-back/back-to-front airflow for hot/cold aisles, rear rack mounts, and redundant hot-swappable AC or DC power and fans

Manageability

- **Full-featured console**
provides complete control of the switch with a familiar CLI
- **Web interface**
allows configuration of the switch from any Web browser on the network
- **RMON and sFlow**
provide advanced monitoring and reporting capabilities for statistics, history, alarms, and events

Overview

- **Multiple configuration files**
allow multiple configuration files to be stored to a flash image
- **Troubleshooting**
 - **Ingress and egress port monitoring**
enable network problem solving
 - **Traceroute and ping**
enable testing of network connectivity
 - **Virtual cable tests**
provide visibility to cable problems

Layer 2 switching

- **32K MAC addresses**
provide access to many Layer 2 devices
- **4,094 port-based VLANs**
provide security between workgroups
- **IEEE 802.1ad QinQ and Selective QinQ**
increase the scalability of an Ethernet network by providing a hierarchical structure; connect multiple LANs on a high-speed campus or metro network
- **Gigabit Ethernet port aggregation**
allows grouping of ports to increase overall data throughput to a remote device
- **10 GbE port aggregation**
allows grouping of ports to increase overall data throughput to a remote device
- **Spanning Tree/MSTP, RSTP, and STP Root Guard**
prevent network loops
- **sFlow**
allows traffic sampling
- **GVRP VLAN Registration Protocol**
allows automatic learning and dynamic assignment of VLANs

Layer 3 services

- **Address Resolution Protocol (ARP)**
determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **Dynamic Host Configuration Protocol (DHCP)**
simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Layer 3 routing

- **Layer 3 IPv4 routing**
provides routing of IPv4 at media speed; supports static routes, RIP and RIPv2, OSPF, IS-IS, and BGP
- **Routing Information Protocol (RIP) and RIPv2 support**
provides complete support of RIP for both IPv4 and IPv6
- **OSPF and OSPFv3 support**
provides complete support of OSPF for both IPv4 and IPv6
- **IS-IS and IS-ISv6 support**
provides complete support of IS-IS for both IPv4 and IPv6
- **Layer 3 IPv6 routing**
provides routing of IPv6 at media speed; supports static routes, RIPv2, OSPFv3, IS-ISv6, and BGP4+
- **Bidirectional Forwarding Detection (BFD)**
enables link connectivity monitoring and reduces network convergence time for RIP, OSPF, BGP, IS-IS, VRRP, MPLS, and

Overview

IRF

- **Virtual Router Redundancy Protocol (VRRP) and VRRP Extended**
allow quick failover of router ports
- **Policy-based routing**
makes routing decisions based on policies set by the network administrator
- **IGMPv1, v2, and v3**
allow individual hosts to be registered on a particular VLAN
- **PIM-SSM, PIM-DM, and PIM-SM (for IPv4 and IPv6)**
support IP Multicast address management and inhibition of DoS attacks
- **Equal-Cost Multipath (ECMP)**
enables multiple equal-cost links in a routing environment to increase link redundancy and scale bandwidth

Security

- **Defense-in-depth security**
provides integrated and distributed security enforcement that can be managed from a central location, such as the HP Intelligent Management Center (IMC)
- **Advanced processor queuing mechanism**
helps prevent denial-of-service (DoS) attacks, while DHCP snooping helps ensure that devices can only receive an IP address from a legitimate DHCP server on the network
- **RADIUS/HWTACACS**
eases switch management security administration by using a password authentication server
- **Secure Shell (SSHv2)**
encrypts all transmitted data for secure, remote CLI access over IP networks
- **IEEE 802.1X-based dynamic delivery of QoS, ACLs, and VLANs**
allows complete control over user network access
- **Guest VLAN**
provides a browser-based environment to authenticated clients that is similar to IEEE 802.1X
- **Port isolation**
secures and adds privacy, and prevents malicious attackers from obtaining user information
- **Port security**
allows access only to specified MAC addresses, which can be learned or specified by the administrator
- **MAC-based authentication**
allows or denies access to the switch based on a client MAC address
- **IP Source Guard**
helps prevent IP spoofing attacks
- **HTTPS management**
provides secure Web management
- **Unicast Reverse Path Forwarding (URPF)**
limits malicious traffic on a network
- **Multi-Customer Edge (MCE)-Multicast Virtual Routing and Forwarding (MVRF)**
provide MPLS Edge router support
- **Public Key Infrastructure (PKI)**
is used to control access

Convergence

- **Voice VLAN**
automatically assigns VLAN and priority for IP phones, simplifying network configuration and maintenance
- **LLDP-MED**
is a standard extension that automatically configures network devices, including LLDP-capable IP phones
- **Internet Group Management Protocol (IGMP)**
utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks; supports IGMPv1, v2, and v3

Overview

- **Protocol Independent Multicast (PIM)**
defines modes of Internet multicasting to allow one-to-many and many-to-many transmission of information; supports PIM Dense Mode (DM), Sparse Mode (SM), and Source-Specific Mode (SSM)

Monitor and diagnostics

- **Port mirroring**
enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- **OAM (802.3ah)**
operations, administration and maintenance (OAM) management capability detects data link layer problems that occurred in the "last mile"; monitors the status of the link between the two devices
- **CFD (802.1ag)**
connectivity fault detection (CFD) provides a Layer 2 link OAM (operations, administration, and maintenance) mechanism used for link connectivity detection and fault locatin

Additional information

- **Intelligent Resilient Framework (IRF)**
 - Creates virtual resilient switching fabrics, where two or more switches perform as a single Layer 2 switch and Layer 3 router
 - Does not require switches to be co-located and allows them to be part of a disaster-recovery system
 - Allows servers or switches to be attached using standard LACP for automatic load balancing and high availability
 - Simplifies network operation by eliminating the complexity of Spanning Tree Protocol, ECMP, or VRRP
- **OAA modules**
support wireless network management and high-performance security applications; leverage network infrastructure investment
- **Green IT and power**
improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs
- **High scalability with IRF**
HP Intelligent Resilient Framework (IRF) technology simplifies the architecture of server access networks; up to nine HP 5820/5820AF stackable switches can be combined to deliver unmatched scalability of virtualized access layer switches and flatter, two-tier FlexFabric networks using IRF, which reduces cost and complexity

Warranty and support

- **1-year warranty**
with advance replacement and 10-calendar-day delivery (available in most countries)
- **Electronic and telephone support**
limited electronic and business-hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to www.hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to www.hp.com/networking/warrantysummary
- **Software releases**
to find software for your product, refer to www.hp.com/networking/support; for details on the software releases available with your product purchase, refer to www.hp.com/networking/warrantysummary

Configuration

Build To Order: BTO is a standalone unit with no integration. BTO products ship standalone are not part of a CTO or Rack-Shippable solution.

Standard Switch Chassis

HP 5820-14XG-SFP+ Switch with 2 Slots

- 4 RJ-45 autosensing 10/100/1000 ports
- 2 module slots
- 14 fixed 1000/10000 SFP+ ports
- min=0 \ max=14 SFP+ Transceivers
- 1 Power Supply Required
- 2U - Height

JC106B
See
Configuration
Note:1

HP 5820-24XG-SFP+ Switch

- 4 RJ-45 autosensing 10/100/1000 ports
- 24 fixed 1000/10000 SFP+ ports
- min=0 \ max=24 SFP+ Transceivers
- 1 Power Supply Required
- 1U - Height

JC102B
See
Configuration
Note:1

HP 5820AF-24XG Switch

- 4 RJ-45 autosensing 10/100/1000 ports
- 24 fixed 1000/10000 SFP+ ports
- min=0 \ max=24 SFP+ Transceivers
- 1 Power Supply Required
- 2 Fan Trays Required
- 1U - Height

JG219B
See
Configuration
Note:1

Configuration Rules:

Note 1 The following Transceivers install into this Switch (Max = 14 or 24 depending on Switch) (Use #0D1 or #B01 if switch is CTO):

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP RJ45 T Transceiver	JD089B

Configuration

Box Level Integration CTO Models

CTO Solution Sku

HP 58xx CTO Switch Solution	JG478A
<ul style="list-style-type: none"> SSP trigger sku 	

CTO Base Sku

HP 5820-14XG-SFP+ w/2 Slots CTO Switch	JC106BC
<ul style="list-style-type: none"> 4 RJ-45 autosensing 10/100/1000 ports 2 module slots 14 fixed 1000/10000 SFP+ ports min=0 \ max=14 SFP+ Transceivers 1 Power Supply Required 2U - Height 	See Configuration Note:1,4

HP 5820-24XG-SFP+ CTO Switch	JC102BC
<ul style="list-style-type: none"> 4 RJ-45 autosensing 10/100/1000 ports 24 fixed 1000/10000 SFP+ ports min=0 \ max=24 SFP+ Transceivers 1 Power Supply Required 1U - Height 	See Configuration Note:1,4

HP 5820AF-24XG Switch	JG219B
<ul style="list-style-type: none"> 4 RJ-45 autosensing 10/100/1000 ports 24 fixed 1000/10000 SFP+ ports (min=0 \ max=24 SFP+ Transceivers) 1 Power Supply Required 2 Fan Trays Required 1U - Height 	See Configuration Note:1, 4

Configuration Rules:

Note 1	The following Transceivers install into this Switch (Max = 14 or 24 depending on Switch): (Use #0D1 if switch is CTO)
	HP X130 10G SFP+ LC SR Transceiver JD092B
	HP X130 10G SFP+ LC LRM Transceiver JD093B
	HP X130 10G SFP+ LC LR Transceiver JD094B
	HP X130 10G SFP+ LC ER 40km Transceiver JG234A
	HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable JD095C
	HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable JD096C
	HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable JD097C
	HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable JG081C
	HP X125 1G SFP LC LH40 1310nm Transceiver JD061A
	HP X120 1G SFP LC LH40 1550nm Transceiver JD062A
	HP X125 1G SFP LC LH70 Transceiver JD063B

Configuration

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP RJ45 T Transceiver	JD089B

Note 4 If the Switch Chassis is to be Box Level Factory Integrated (CTO), Then the #0D1 is required on the Switch Chassis and integrated to the JG478A - HP 58xx CTO Enablement. (Max 1 switch per SSP)

Rack Level Integration CTO Models

Standard Switch Chassis

HP 5820-14XG-SFP+ Switch with 2 Slots

- 4 RJ-45 autosensing 10/100/1000 ports
- 2 module slots
- 14 fixed 1000/10000 SFP+ ports
- min=0 \ max=14 SFP+ Transceivers
- 1 Power Supply Required
- 2U - Height

JC106B
See
Configuration
Note:1, 11

HP 5820-24XG-SFP+ Switch

- 4 RJ-45 autosensing 10/100/1000 ports
- 24 fixed 1000/10000 SFP+ ports
- min=0 \ max=24 SFP+ Transceivers
- 1 Power Supply Required
- 1U - Height

JC102B
See
Configuration
Note:1, 11

HP 5820AF-24XG Switch

- 4 RJ-45 autosensing 10/100/1000 ports
- 24 fixed 1000/10000 SFP+ ports (min=0 \ max=24 SFP+ Transceivers)
- 1 Power Supply Required
- 2 Fan Trays Required
- 1U - Height

JG219B
See
Configuration
Note:1, 11

Configuration Rules:

Note 1 The following Transceivers install into this Switch (Max = 14 or 24 depending on Switch):

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B

Configuration

HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X120 1G SFP RJ45 T Transceiver	JD089B

Note 11 If HP CTO Switch Chassis is selected for Rack Level Integration, Then the Switch needs to integrate (with #0D1) to the HP Rack.

Enter the following menu selections as integrated to the CTO Model X server above if order is factory built.

Modules

Ethernet Modules

(JC106x and JG259x Switch Only) System (std 0 // max 2) User Selection (min 0 // max 2) per chassis

HP 5800 4-port 10GbE SFP+ Module	JC091A
<ul style="list-style-type: none"> min=0 \ max=4 SFP + Transceivers 	See Configuration Note:1
HP 5800 2-port 10GbE SFP+ Module	JC092B
<ul style="list-style-type: none"> min=0 \ max=2 SFP + Transceivers 	See Configuration Note:1
HP 5820 4-port 8/4/2 Gbps FCoE SFP+ Mod	JC530A
<ul style="list-style-type: none"> min=0 \ max=4 SFP + Transceivers 	See Configuration Note:1

Configuration Rules:

Note 1 The following Transceivers install into this Module: (Use #0D1 or #B01 if switch is CTO)

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C

Access Control Modules

(JC106x and JG259x Switch Only) System (std 0 // max 1) User Selection (min 0 // max 1) per chassis

HP A5800 Access Controller Module for 32-64 Aps	JD443A
<ul style="list-style-type: none"> No Transceivers 	

Configuration

HP 5820 VPN Firewall Module	JD255A
<ul style="list-style-type: none"> No Transceivers 	

Configuration Rules:

Note 1	This Module only installs into the following switches:	
	HP 5820X-14XG-SFP+ Switch w 2 Intf SIts	JC106x
	HP 5820X-14XG-SFP+ TAA Switch w 2 Slots	JG259x

Transceivers

SFP+ Transceivers

HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ SFP+ 0.65m DAC Cable	JD095C#B01
HP X240 10G SFP+ SFP+ 1.2m DAC Cable	JD096C#B01
HP X240 10G SFP+ SFP+ 3m DAC Cable	JD097C#B01
HP X240 10G SFP+ SFP+ 5m DAC Cable	JG081C#B01

SFP Transceivers

HP X125 1G SFP LC LH40 1310nm XCVR	JD061A
HP X120 1G SFP LC LH40 1550nm XCVR	JD062A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP RJ45 T Transceiver	JD089B

Internal Power Supplies

System (std 0 // max 2) User Selection (min 1 // max 2) per switch enclosure

HP A5800 300W DC Power Supply	JC090A See Configuration Note:1, 2
HP A5800 300W AC Power Supply	JC087A See Configuration Note:1, 2, 3
<ul style="list-style-type: none"> includes 1 x c13, 300w 	
PDU Cable NA/MEX/TW/JP	JC087A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	

Configuration

PDU Cable ROW	JC087A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
HP A58x0AF 650W AC Power Supply	JC680A
<ul style="list-style-type: none"> includes 1 x c13, 650w 	See Configuration Note:1, 3, 5
PDU Cable NA/MEX/TW/JP	JC680A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable ROW	JC680A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
HP 58x0AF 650W DC Power Supply	JC681A
	See Configuration Note:1, 5
HP A58x0AF 300W AC Power Supply	JG900A
<ul style="list-style-type: none"> includes 1 x c13, 300w 	See Configuration Note:1, 3, 5
PDU Cable NA/MEX/TW/JP	JG900A#B2B
<ul style="list-style-type: none"> C15 PDU Jumper Cord (NA/MEX/TW/JP) 	
PDU Cable ROW	JG900A#B2C
<ul style="list-style-type: none"> C15 PDU Jumper Cord (ROW) 	
High Volt Switch/Router to Wall Power Cord	JG900A#B2E
<ul style="list-style-type: none"> NEMA L6-20P Cord (NA/MEX/JP/TW) 	
HP A58x0AF 300W DC Power Supply	JG901A
	See Configuration Note:1,5

Configuration Rules:

- Note 1 If 2 power supplies are selected they must be the same Sku number.
- Note 2 Supported only on the JC102B, JC106B, JG243B and JG259B Switches
- Note 3 Localization (Wall Power Cord) required on orders without #B2B, #B2C (PDU Power Cord) . (See Localization Menu)
REMARK: When Switches/Routers are Factory Racked, Then #B2B, or #B2C should be the Defaulted Power Cable option on the Switches/Routers.
- Note 5 Supported only on the JG219B Switch

Configuration

Remarks:

Drop down under power supply should offer the following options and results:
Switch/Router/Power Supply to PDU Power Cord - #B2B in North America, Mexico, Taiwan, and Japan or #B2C ROW. (Watson Default B2B or B2C for Rack Level CTO)
Switch/Router/Power Supply to Wall Power Cord - Localized Option (Watson Default for BTO and Box Level CTO)

NOTE* Switch JG219B should default selection of Power Supply as JC680A but allow selection of JG900A, JG901A, and JC681A.

Switch Options

Fan Trays

(JG219B only) System (std 0 // max 2) User Selection (min 2 // max 2) per switch

HP 58x0AF Bck(pwr)-Frt(ports) Fan Tray

JC682A
See
Configuration
Note:1

HP 58x0AF Frt(ports)-Bck(pwr) Fan Tray

JC683A
See
Configuration
Note:1

Configuration Rules:

Note 1 Fan Trays cannot be mixed in the same switch enclosure

Remarks: Watson Blue Text:

If there is any empty space below the switch in a rack when using Back to Front Fan Trays, JC682A, the rack will receive an Air Plenum kit that takes up 1U of additional space in the rack. The Air Plenum kit is not required on fully configured racks. This only applies for CTO Rack Level Integration. The Air Plenum Kit is a non-saleable SKU, and is brought in automatically for CTO Factory Rack Level Integration.

Opacity Shield Kit

HP 5800-24XG-SFP+ Opcty Shld Kit

- Supported on JG243B

JG564A#B01
See
Configuration
Note:1

Configuration Rules:

Note 1 If selected with a CTO Switch Solution, Quantity 1 of JG585A#B01 must also be ordered.

Tamper Evidence Labels

Configuration

HP 12mm x 60mm Tmpr-Evidence (30) Lbl

- Supported on JG243B

JG585A#B01
See
Configuration
Note:1

Configuration Rules:

Note 1 If selected with a CTO Switch Solution, Quantity 1 of JG564A#B01 must also be ordered.

External Redundant Power Supplies

HP RPS1600 Redundant Power System

- Height = 1U
- includes 1 x c13, 1600w and Power Supply port

JG136A
See
Configuration
Note:2, 3, 5

HP RPS1600 1600W AC Power Supply

- Installs into JG136A only

JG137A
See
Configuration
Note:1, 3

Configuration Rules:

Note 1 If this power supply is selected, The JG136A - HP A-RPS1600 Redundant Power System must be on order or onsite.

Note 2 Localization required.

Note 3 Each switch will only support 1 JG136A and 1 JG137A Power supply systems.

Note 5 This power supply only supported on switches JC102B and JC106B.

Options for the HP RPS1600 Redundant Power System

HP X290 1000 A JD5 2m RPS Cable

JD187A
See
Configuration
Note:3

HP X290 1000 B JD5 2m RPS Cable

JD189A
See
Configuration
Note:4

Remarks:

These cables are used to connect the External Power System to Switch.

Configuration Rules:

Note 3 This Cable is only supported on switches JC102B and, JC106B when used with the RPS 1600 (JG136A).

Configuration

Note 4 This Cable is only supported on switches JC102B and JC106B when used with the RPS 1600 (JG136A)

Technical Specifications

HP 5820-14XG-SFP+ Switch with 2 Slots (JC106B)

Ports	14 SFP+ 10-GbE ports; Duplex: full only	
	2 extended module slots	
	1 open module slot	
	4 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)	
	1 RJ-45 serial console port	
	Supports a maximum of 14 SFP+ ports plus 8 8/4/2 Gbps Fibre Channel SFP+ ports, with optional module	
Additional ports and slots	1 RJ-45 serial console port	
Power supplies	2 power-supply slots	
	1 minimum power-supplies required (ordered separately)	
Fan tray	includes: 1 x JC096A	
	1 fan tray slot	
	Base product includes fan tray	
Physical characteristics	Dimensions	17.32(w) x 18.39(d) x 3.39(h) in (43.99 x 46.7 x 8.61 cm) (2U height)
	Weight	33.29 lb (15.1 kg)
Memory and processor	2048 MB SDRAM; Packet buffer size: 2 MB, 512 MB flash	
Performance	Latency	2.02 μ s (Cut Through) 2.02 μ s, (Store and Forward) (64-byte packets)
	Throughput	up to 363 Mpps (64-byte packets)
	Routing/Switching capacity	488 Gbps
	Routing table size	12000 entries (IPv4)
	MAC address table size	32000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Acoustic	Low-speed fan: 44.3 dB, High-speed fan: 54.1 dB
Electrical characteristics	Maximum heat dissipation	836 BTU/hr (881.98 kJ/hr)
	Voltage	100 - 120 / 200 - 240 VAC, rated -48 to -60 VDC, rated (depending on power supply chosen)
	Maximum power rating	300 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance	
Emissions	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
Immunity	Generic	ETSI EN 300 386 V1.3.3

Technical Specifications

	EN	EN 55024:1998+ A1:2001 + A2:2003
	ESD	EN 61000-4-2; IEC 61000-4-2
	Radiated	EN 61000-4-3; IEC 61000-4-3
	EFT/Burst	EN 61000-4-4; IEC 61000-4-4
	Surge	EN 61000-4-5; IEC 61000-4-5
	Conducted	EN 61000-4-6; IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8; EN 61000-4-8
	Voltage dips and interruptions	EN 61000-4-11; IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP	
Notes	The customer must order a power supply, as the device does not come with a PSU. At least one JC087A or JC090A is required.	
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

HP 5820X-24XG-SFP+ Switch (JC102B)

Ports	24 SFP+ 10-GbE ports; Duplex: full only 4 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) Supports a maximum of 24 SFP+ ports plus 4 autosensing 10/100/1000 ports	
Additional ports and slots	1 RJ-45 serial console port	
Power supplies	2 power-supply slots 1 minimum power-supplies required (ordered separately)	
Fan tray	includes: 1 x JC098A 1 fan tray slot Base product includes fan tray	
Physical characteristics	Dimensions	17.32(w) x 16.81(d) x 1.73(h) in (44.0 x 42.7 x 4.4 cm) (1U height)
	Weight	18.74 lb (8.5 kg)
Memory and processor	2048 MB SDRAM; Packet buffer size: 2 MB, 512 MB flash	
Performance	Latency	2.02 μ s (Cut Through) 2.02 μ s, (Store and Forward) (64-byte packets)
	Throughput	up to 363 million pps (64-byte packets)
	Routing/Switching capacity	488 Gbps
	Routing table size	12000 entries (IPv4)
	MAC address table size	32000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Acoustic	Low-speed fan: 48.4 dB, High-speed fan: 59.7 dB
Electrical characteristics	Maximum heat dissipation	631 BTU/hr (665.71 kJ/hr)

Technical Specifications

	Voltage	100 - 120 / 200 - 240 VAC, rated -48 to -60 VDC, rated (depending on power supply chosen)
	Maximum power rating	300 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety		UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance
Emissions		VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A
Immunity	Generic	ETSI EN 300 386 V1.3.3
	EN	EN 55024:1998+ A1:2001 + A2:2003
	ESD	EN 61000-4-2; IEC 61000-4-2
	Radiated	EN 61000-4-3; IEC 61000-4-3
	EFT/Burst	EN 61000-4-4; IEC 61000-4-4
	Surge	EN 61000-4-5; IEC 61000-4-5
	Conducted	EN 61000-4-6; IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8; EN 61000-4-8
	Voltage dips and interruptions	EN 61000-4-11; IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
	Flicker	EN 61000-3-3, IEC 61000-3-3
Management		IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP
Notes		The customer must order a power supply, as the device does not come with a PSU. At least one JC087A or JC090A is required.
Services		Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5820AF-24XG Switch (JG219B)

Ports	24 fixed 1000/10000 SFP+ ports 2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only
Additional ports and slots	1 RJ-45 serial console port 1 RJ-45 out-of-band management port 1 USB 2.0
Power supplies	2 power-supply slots 1 minimum power-supplies required (ordered separately)
Fan tray	2 fan tray slots The customer must order fan trays, as fan trays are not included with the switch. This system requires two same-direction airflow fan trays to function properly. The system should not be operated with only one fan tray for more than 24 hours. The system should not be operated without a fan tray more than two minutes. The system should not be operated outside of the temperature range of 32°F (0°C)

Technical Specifications

to 113°F (45°C). Failure to comply with these operating requirements may void the product warranty.

Physical characteristics	Dimensions	25.98(w) x 17.32(d) x 1.72(h) in (65.99 x 43.99 x 4.37 cm) (1U height)
	Weight	22.05 lb (10 kg), Fully loaded
Memory and processor	2048 MB flash; Packet buffer size: 2 MB, 512 MB SDRAM	
Performance	Latency	3 μs(64-byte packets)
	Throughput	up to 360 Mpps
	Routing/Switching capacity	484 Gbps
	Routing table size	12000 entries (IPv4)
	MAC address table size	32000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	10% to 90%, noncondensing
	Acoustic	Low-speed fan: 60.1 dB, High-speed fan: 69.9 dB
Electrical characteristics	Maximum heat dissipation	607 BTU/hr (640.39 kJ/hr)
	Voltage	100 - 120 / 200 - 240 VAC, rated -48 to -60 VDC, rated (depending on power supply chosen)
	Maximum power rating	650 W
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; ULAR; GOST; EN 60950-1/A11; FDA 21 CFR Subchapter J; NOM; ROHS Compliance	
Emissions	VCCI Class A; EN 55022 Class A; ICES-003 Class A; ANSI C63.4 2003; AS/NZS CISPR 22 Class A; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; FCC (CFR 47, Part 15) Class A	
Immunity	Generic	ETSI EN 300 386 V1.3.3
	EN	EN 55024:1998+ A1:2001 + A2:2003
	ESD	EN 61000-4-2; IEC 61000-4-2
	Radiated	EN 61000-4-3; IEC 61000-4-3
	EFT/Burst	EN 61000-4-4; IEC 61000-4-4
	Surge	EN 61000-4-5; IEC 61000-4-5
	Conducted	EN 61000-4-6; IEC 61000-4-6
	Power frequency magnetic field	IEC 61000-4-8; EN 61000-4-8
	Voltage dips and interruptions	EN 61000-4-11; IEC 61000-4-11
	Harmonics	EN 61000-3-2, IEC 61000-3-2
Flicker	EN 61000-3-3, IEC 61000-3-3	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP	
Notes	The customer must order power supply, as the device does not come with a PSU. At least one JC680A or JC681A is required	
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level	

Technical Specifications

descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

General protocols

IEEE 802.1ag Service Layer OAM
 IEEE 802.1D MAC Bridges
 IEEE 802.1p Priority
 IEEE 802.1Q VLANs
 IEEE 802.1s (MSTP)
 IEEE 802.1v VLAN classification by Protocol and Port
 IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 IEEE 802.3ad Link Aggregation Control Protocol (LACP)
 IEEE 802.3ae 10-Gigabit Ethernet
 IEEE 802.3x Flow Control
 RFC 768 UDP
 RFC 792 ICMP
 RFC 793 TCP
 RFC 826 ARP
 RFC 854 TELNET
 RFC 925 Multi-LAN Address Resolution
 RFC 951 BOOTP
 RFC 1058 RIPv1
 RFC 1350 TFTP Protocol (revision 2)
 RFC 1519 CIDR
 RFC 1542 BOOTP Extensions
 RFC 2131 DHCP
 RFC 2453 RIPv2
 RFC 3046 DHCP Relay Agent Information Option
 RFC 3576 Ext to RADIUS (CoA only)
 RFC 3768 VRRP
 RFC 4675 RADIUS VLAN & Priority
 RFC3323 A Privacy Mechanism for the Session Initiation Protocol (SIP)
 802.1r - GARP Proprietary Attribute Registration Protocol (GPRP)

IP multicast

RFC 2934 Protocol Independent Multicast MIB for IPv4
 RFC 3376 IGMPv3 (host joins only)
 RFC 3618 Multicast Source Discovery Protocol (MSDP)
 RFC 3973 Draft 2 PIM Dense Mode
 RFC 4601 Draft 10 PIM Sparse Mode

IPv6

RFC 2080 RIPng for IPv6
 RFC 2460 IPv6 Specification
 RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 RFC 2740 OSPFv3 for IPv6
 RFC 2925 Remote Operations MIB (Ping only)
 RFC 3019 MLDv1 MIB

RFC 4443 ICMPv6
 RFC 4541 IGMP & MLD Snooping Switch
 RFC 4861 IPv6 Neighbor Discovery
 RFC 4862 IPv6 Stateless Address Auto-configuration

MIBs

IEEE8021-PAE-MIB
 IEEE8023-LAG-MIB
 RFC 1213 MIB II
 RFC 1493 Bridge MIB
 RFC 1657 BGP-4 MIB
 RFC 1724 RIPv2 MIB
 RFC 1850 OSPFv2 MIB
 RFC 2011 SNMPv2 MIB for IP
 RFC 2013 SNMPv2 MIB for UDP
 RFC 2233 Interface MIB
 RFC 2273 SNMP-NOTIFICATION-MIB
 RFC 2452 IPV6-TCP-MIB
 RFC 2454 IPV6-UDP-MIB
 RFC 2465 IPv6 MIB
 RFC 2466 ICMPv6 MIB
 RFC 2571 SNMP Framework MIB
 RFC 2572 SNMP-MPD MIB
 RFC 2573 SNMP-Notification MIB
 RFC 2618 RADIUS Client MIB
 RFC 2620 RADIUS Accounting MIB
 RFC 2665 Ethernet-Like-MIB
 RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 RFC 2688 MAU-MIB
 RFC 2787 VRRP MIB
 RFC 2819 RMON MIB
 RFC 2925 Ping MIB
 RFC 3414 SNMP-User based-SM MIB
 RFC 3415 SNMP-View based-ACM MIB
 RFC 3418 MIB for SNMPv3
 RFC 3621 Power Ethernet MIB
 RFC 3826 AES for SNMP's USM MIB
 RFC 4133 Entity MIB (Version 3)
 LLDP-EXT-DOT1-MIB
 LLDP-EXT-DOT3-MIB
 LLDP-MIB

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
 RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)
 RFC 3176 sFlow
 ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
 SNMPv1/v2c/v3

OSPF

Technical Specifications

RFC 3162 RADIUS and IPv6
RFC 3315 DHCPv6 (client and relay)
RFC 3315 DHCPv6 (client only)
RFC 3810 MLDv2 (host joins only)
RFC 4022 MIB for TCP
RFC 4251 SSHv6 Architecture
RFC 4252 SSHv6 Authentication
RFC 4253 SSHv6 Transport Layer
RFC 4254 SSHv6 Connection
RFC 4293 MIB for IP
RFC 4419 Key Exchange for SSH

RFC 2328 OSPFv2
RFC 3101 OSPF NSSA

Security

IEEE 802.1X Port Based Network Access Control
RFC 1492 TACACS+
RFC 2865 RADIUS (client only)
RFC 2866 RADIUS Accounting
Secure Sockets Layer (SSL)
SSHv2 Secure Shell

Accessories

HP 5820 Switch Series accessories

Transceivers

HP X125 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B
HP X120 1G SFP RJ45 T Transceiver	JD089B
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X130 10G SFP+ LC SR Transceiver	JD092B
HP X130 10G SFP+ LC LRM Transceiver	JD093B
HP X130 10G SFP+ LC LR Transceiver	JD094B
HP X130 10G SFP+ LC ER 40km Transceiver	JG234A
HP X240 10G SFP+ to SFP+ 0.65m Direct Attach Copper Cable	JD095C
HP X240 10G SFP+ to SFP+ 1.2m Direct Attach Copper Cable	JD096C
HP X240 10G SFP+ to SFP+ 3m Direct Attach Copper Cable	JD097C
HP X240 10G SFP+ to SFP+ 5m Direct Attach Copper Cable	JG081C
HP X240 40G QSFP+ to 4x10G SFP+ 1m Direct Attach Copper Splitter Cable	JG329A
HP X240 40G QSFP+ to 4x10G SFP+ 3m Direct Attach Copper Splitter Cable	JG330A
HP X240 40G QSFP+ to 4x10G SFP+ 5m Direct Attach Copper Splitter Cable	JG331A

Cables

HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable	QK732A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable	QK733A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable	QK734A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable	QK735A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable	QK736A
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable	QK737A

Power Supply

HP RPS1600 Redundant Power System	JG136A
HP RPS1600 1600W AC Power Supply	JG137A

HP 5820-24XG-SFP+ Switch (JC102B)

HP 5800 300W AC Power Supply	JC087A
HP 5800 300W DC Power Supply	JC090A
HP 5800 1RU Spare Fan Assembly	JC098A

HP 5820-14XG-SFP+ Switch with 2 Interface Slots & 1 OAA Slot (JC106B)

HP 5800 4-port 10GbE SFP+ Module	JC091A
HP 5800 2-port 10GbE SFP+ Module	JC092B

HP 5800 300W AC Power Supply (JC087A)

HP 5800 300W DC Power Supply	JC090A
HP 5800 2RU Spare Fan Assembly	JC096A
HP 5820 VPN Firewall Module	JD255A

HP 5820AF-24XG Switch (JG219B)

HP A58x0AF 650W AC Power Supply	JC680A
HP 58x0AF 650W DC Power Supply	JC681A

Accessories

HP A58x0AF Back (power side) to Front (port side) Airflow Fan Tray	JC682A
HP A58x0AF Front (port side) to Back (power side) Airflow Fan Tray	JC683A

Accessory Product Details

NOTE: Details are not available for all accessories. The following specifications were available at the time of publication.

HP X124 1G SFP LC LH40 1310nm Transceiver (JD061A) A small form-factor pluggable SFP Gigabit LH40 transceiver that provides a full duplex Gigabit solution up to 40km on a single-mode fiber.	Ports	1 LC 1000Base-LH port (no IEEE standard exists for 1550 nm optics)
	Connectivity	Connector type Wavelength
	Physical characteristics	Dimensions
	Electrical characteristics	Full configuration weight Power consumption typical Power consumption maximum
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: <ul style="list-style-type: none"> 40km distance
	Services	Fiber type Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A) A small form-factor pluggable (SFP) Gigabit LH40 transceiver that provides a full-duplex Gigabit solution up to 40 km on a single mode fiber.	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
	Connectivity	Connector type Wavelength
	Physical characteristics	Dimensions
	Electrical characteristics	Full configuration weight Power consumption typical Power consumption maximum
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652; Maximum distance: <ul style="list-style-type: none"> 40km distance
	Services	Fiber type Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP X125 1G SFP LC LH70	Ports	1 LC 1000BASE-LH port (no IEEE standard exists for 1550 nm optics)
	Connectivity	Connector type LC

Accessory Product Details

Transceiver (JD063B) A small form-factor pluggable (SFP) Gigabit LH70 transceiver that provides a full-duplex Gigabit solution up to 70km on a single-mode fiber.	Physical characteristics	Wavelength	1550 nm
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)
		Full configuration weight	0.04 lb. (0.02 kg)
	Electrical characteristics	Power consumption typical	0.8 W
		Power consumption maximum	1.0 W
	Cabling	Cable type: Single-mode fiber optic, complying with ITU-T G.652;	
Services	Maximum distance: • 70km Fiber type Single Mode Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.		

HP X125 1G SFP RJ45 T Transceiver (JD089B) A small form factor pluggable (SFP) Gigabit 1000Base-T transceiver that provides a full duplex Gigabit solution up to 100m on a Cat-5+ cable.	Ports	1 RJ-45 1000BASE-T port (IEEE 802.3ab Type 1000BASE-T)		
	Connectivity	Connector type	RJ-45	
	Physical characteristics	Dimensions	2.71(d) x 0.54(w) x 0.55(h) in. (6.88 x 1.37 x 1.4 cm)	
		Full configuration weight	0.07 lb. (0.03 kg)	
	Electrical characteristics	Power consumption typical	0.8 W	
		Power consumption maximum	1.0 W	
Cabling	Cable type: 1000BASE-T: Category 5 (5E or better recommended), 100 Û differential 4-pair unshielded twisted pair (UTP) or shielded twisted pair (STP) balanced, complying with IEEE 802.3ab 1000BASE-T;			
Services	Maximum distance: • 100m Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.			

HP X120 1G SFP LC SX Transceiver (JD118B) A small form-factor pluggable (SFP) Gigabit SX transceiver that provides a full-duplex Gigabit solution up to 550m on a Multimode fiber.	Ports	1 LC 1000BASE-SX port		
	Connectivity	Connector type	LC	
	Physical characteristics	Wavelength	850 nm	
		Dimensions	2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)	
	Electrical characteristics	Full configuration weight	0.04 lb. (0.02 kg)	
		Power consumption typical	0.8 W	
Cabling	Power consumption maximum	1.0 W		
	Maximum distance: • FDDI Grade distance = 220m • OM1 = 275m			

Accessory Product Details

Services	<ul style="list-style-type: none"> • OM2 = 500m • OM3 = Not Specified by standard <p>Cable length up to 550m</p> <p>Fiber type Multi Mode</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
-----------------	--

<p>HP X120 1G SFP LC LX Transceiver (JD119B)</p> <p>A small form-factor pluggable (SFP) Gigabit LX transceiver that provides a full duplex Gigabit solution up to 550m on MMF or 10Km on SMF</p>	<p>Ports</p> <p>1 SFP 1000BASE-LX port (IEEE 802.3z Type 1000BASE-LX)</p> <p>Connectivity</p> <p>Connector type LC</p> <p>Wavelength 1300 nm</p> <p>Physical characteristics</p> <p>Dimensions 2.17(d) x 0.6(w) x 0.46(h) in. (5.51 x 1.52 x 1.17 cm)</p> <p>Full configuration weight 0.04 lb. (0.02 kg)</p> <p>Electrical characteristics</p> <p>Power consumption typical 0.8 W</p> <p>Power consumption maximum 1.0 W</p> <p>Cabling</p> <p>Cable type: Either single mode or multimode;</p> <p>Maximum distance:</p> <ul style="list-style-type: none"> • 550m for Multimode • 10km for Singlemode <p>Fiber type Both</p> <p>Services</p> <p>Refer to the HP website at www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>
---	---

<p>HP RPS1600 Redundant Power System (JG136A)</p>	<p>Ports</p> <p>8 redundant power supply ports Restrictions: two -56V/25A DC(PoE); six -56V/8A DC(non-PoE)</p> <p>Physical characteristics</p> <p>Dimensions 15.63(d) x 17.32(w) x 1.74(h) in. (39.7 x 44 x 4.42 cm)</p> <p>Weight 14.11 lb. (6.4 kg)</p> <p>Full configuration weight 16.75 lb. (7.6 kg)</p> <p>Environment</p> <p>Operating temperature 14°F to 122°F (-10°C to 50°C)</p> <p>Operating relative humidity 5% to 95%</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 5% to 95%</p> <p>Altitude up to 13,123 ft. (4 km)</p> <p>Acoustic Pressure: 53 dB; ISO 7779, ISO 9296</p> <p>Electrical characteristics</p> <p>Voltage 100-120/200-240 VAC</p> <p>Current 30/60 A</p> <p>Idle power 38 W</p>
--	--

Accessory Product Details

Maximum power rating	3550 W
RPS power	3200 W
PoE power	2800 W
RPS	-55 V
PoE	-55 V
Frequency	50/60 Hz
Notes	<p>Idle power is the actual power consumption of the device with no ports connected.</p> <p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p> <p>With one RPS1600 Power Supply, the PRS1600 Redundant Power System can provide 1600W power output; With two PRS1600 Power Supplies, the output power is 3200W.</p>

Safety	CE Labeled; UL 60950-1; IEC 60950-1; ICES-003; FCC Part 15, Subpart B; EU RoHS Compliant; EN 60950-1/A11; C-Tick; VCCI Class A; ROHS Compliance; EN 300386
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP RPS1600 1600W AC Power Supply (JG137A)

Physical characteristics	Dimensions	8.19(d) x 4.96(w) x 1.63(h) in. (20.8 x 12.6 x 4.15 cm)
	Weight	3.02 lb. (1.37 kg)
Environment	Operating temperature	14°F to 122°F (-10°C to 50°C)
	Operating relative humidity	5% to 95%
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%
Electrical characteristics	Voltage	100-120/200-240 VAC
	Current	15/30 A
	Maximum power rating	1600 W
	Frequency	50/60 Hz
	Notes	<p>Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	

Accessory Product Details

HP 5800 VPN Firewall Module (JD255A)

Ports	2 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 2 dual-personality ports; auto-sensing 10/100/1000Base-T or SFP 1 RJ-45 serial console port 1 Compact Flash port
Physical characteristics	Dimensions 9.84(d) x 9.84(w) x 14.45(h) in. (25 x 25 x 36.7 cm) Weight 7.72 lb. (3.5 kg)
Environment	Operating temperature 32°F to 113°F (0°C to 45°C) Operating relative humidity 10% to 95%, noncondensing
Management	IMC - Intelligent Management Center; command-line interface; Web browser; SNMP Manager; Telnet; HTTPS; RMON1; FTP
Features	Performance - 6.5Gbps Firewall Throughput - 1.8M Concurrent connection - 50K New connection per second - Max 20480 security policies - 2Gbps 3DES/AES VPN Throughput - 5000 IPSec tunnel - 4K VLAN Firewall operation mode - Routing mode - Transparent mode - Hybrid mode AAA service - Local Authentication - Standard Radius - HWTACACS+ - RADIUS domain Authentication ASPF - General TCP / UDP application - FTP/SMTP/HTTP/RTSP/H323 Protocol State Detection - SIP/MGCP/QQ/MSN Protocol State Detection - Java/ActiveX Blocking and Detection - Port mapping - Support for the fragmented packets Virtualization - 256 Virtual Firewall - 4 default Security Zone - Max 256 Security Zone NAT - NAT - PAT - NAT Server - Port mapping - Bidirectional NAT - Static NAT Network Security - Add blacklist by hand or automatically - IP+MAC Binding - ARP Reverse Query - ARP Cheat Check

Accessory Product Details

- Management ports closed by default
- DDOS
 - DNS Query Flood
 - SYN Flood
 - Auto start TCP Proxy when Detect SYN Flood
 - ICMP Flood
 - UDP Flood
 - IP Spoofing
 - SQL injection filter
- L2TP VPN
 - LNS,LAC
 - L2TP Multi-instance
- GRE
 - GRE tunneling protocol
- IPSec
 - AH/ESP
 - ESP
 - Transport/tunnel
 - NAT traversal
 - Strategy template
- IKE
 - DH
 - Pre-share Key authentication-method
 - Support aggressive mode and main exchange mode
 - IKE DPD, PKI / CA
- Network Feature
 - 802.1q VLAN
 - 4K sub-interface
 - Static and dynamic ARP
 - Multicast, PIM
 - IGMP v1/v2/v3
- Routing
 - RIP
 - OSPF
 - BGP
 - Static Route
 - policy Route
- High Availability
 - Active/Active mode
 - Active/Passive mode
 - Session Synchronization for Firewall
- System management
 - Web Management support IE/Firefox
 - Command line interface (Console/Telnet/SSH)
 - Classification Manager
 - Unified management through iMC
 - SNMPv1/v2c/v3
- Administration
 - Software Upgrades
 - Configuration Backup and Restore
- Logging/Monitoring
 - Syslog
 - Mini RMON
 - NTP
 - NAT/ASPF/firewall log stream(Binary log)
- IPv6 Routing & Multicast

Accessory Product Details

- RIPng
- OSPFv3
- BGP4+
- Static Route
- Policy Route
- PIM-SM/DM
- IPv6 Security
 - NAT-PT
 - Manual tunnel
 - IPV6 OVER ipv4 GRE tunnel
 - 6to4 tunnel (RFC3056)
 - ISATAP Tunnel
 - IPv6 Packet Filter
 - Radius
 - NAT64

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

IPv6

- RFC 1981 IPv6 Path MTU Discovery
- RFC 2460 IPv6 Specification
- RFC 2465 Management Information Base for IP Version 6: Textual Conventions and General Group (partially support, only "IPv6 Interface Statistics table")
- RFC 3484 Default Address Selection for IPv6
- RFC 3513 IPv6 Addressing Architecture
- RFC 3587 IPv6 Global Unicast Address Format
- RFC 4007 IPv6 Scoped Address Architecture
- RFC 4862 IPv6 Stateless Address Auto-configuration

Security

- RFC 1321 The MD5 Message-Digest Algorithm
- RFC 1334 PPP Authentication Protocols (PAP)
- RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
- RFC 2104 Keyed-Hashing for Message Authentication
- RFC 2138 RADIUS Authentication
- RFC 2618 RADIUS Authentication Client MIB
- RFC 2620 RADIUS Accounting Client MIB
- RFC 2716 PPP EAP TLS Authentication Protocol
- RFC 2865 RADIUS Authentication
- RFC 2866 RADIUS Accounting
- RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support
- RFC 2868 RADIUS Attributes for Tunnel Protocol Support
- RFC 2869 RADIUS Extensions
- draft-grant-tacacs-02 (TACACS)

VPN

- RFC 1701 Generic Routing Encapsulation (GRE)

- RFC 2405 The ESP DES-CBC Cipher Algorithm With Explicit IV
- RFC 2406 IP Encapsulating Security Payload (ESP)
- RFC 2410 The NULL Encryption Algorithm and Its Use With IPsec
- RFC 2411 IP Security Document Roadmap
- RFC 2451 The ESP CBC-Mode Cipher Algorithms
- RFC 2473 Generic Packet Tunneling in IPv6 Specification
- RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels
- RFC 2661 Layer Two Tunneling Protocol "L2TP"
- RFC 2784 Generic Routing Encapsulation (GRE)
- RFC 2868 RADIUS Attributes for Tunnel Protocol Support
- RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 4214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP)

IKEv1

- RFC 2407 The Internet IP Security Domain of Interpretation for ISAKMP
- RFC 2408 Internet Security Association and Key Management Protocol (ISAKMP).
- RFC 2409 The Internet Key Exchange (IKE)
- RFC 2412 The OAKLEY Key Determination Protocol
- RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE)
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers

PKI

- RFC 2510 Internet X.509 Public Key Infrastructure

Accessory Product Details

RFC 1702 Generic Routing Encapsulation over IPv4 networks.	Certificate Management Protocols
RFC 1828 IP Authentication using Keyed MD5	RFC 2511 Internet X.509 Certificate Request Message Format
RFC 1829 The ESP DES-CBC Transform	RFC 3279 Algorithms and Identifiers for the Internet
RFC 1853 IP in IP Tunneling	X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 2085 HMAC-MD5 IP Authentication with Replay Prevention	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 2401 Security Architecture for the Internet Protocol	draft-nourse-scep-06:
RFC 2402 IP Authentication Header	PKCS#1
RFC 2403 The Use of HMAC-MD5-96 within ESP and AH	PKCS#10
RFC 2404 The Use of HMAC-SHA-1-96 within ESP and AH	PKCS#12
	PKCS#7

HP 5820 4-port 8/4/2 Gbps FCoE SFP+ Module (JC530A)	Physical characteristics	Dimensions	8.27(d) x 6.3(w) x 1.46(h) in. (21 x 16 x 3.7 cm)
		Weight	1.65 lb. (0.75 kg)
	Environment	Full configuration weight	2.76 lb. (1.25 kg)
		Operating temperature	32°F to 113°F (0°C to 45°C)
		Operating relative humidity	5% to 95%
		Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
		Nonoperating/Storage relative humidity	5% to 95%
		Shock and vibration	halt 30g rms
	Notes	Altitude	up to 13,123 ft. (4 km)
		FCoE Features <ul style="list-style-type: none"> • FCoE Compliance: Fibre Channel on Ethernet (FC-BB-5)/ IETF RFC 3643 draft standard • FCoE Support: FIP FCoE initialization protocol/ FIP snooping/ Auto negotiation, full-duplex FC operation/ NPIV transparent connections to FC fabrics • Ethernet Interface Compliance/Support: 10Gbps XAUI ports x 4 (internal)/ ETS - Enhanced transmission Selection (802.1Qaz)/ PFC - Class-based Flow Control (802.1Qbb)/ DCBX (802.1Qbb) • Electrical: Connected and Activity LED controls in Ethernet mode • Fibre Channel Standards: Physical Interface (FC-PI-3)/ Line Services (FC LS)/ Framing & Signaling (FC-FS-2)/ Virtual Interface Architecture Mapping (FC-VI) • Fibre Channel Standards Continued.: Fabric Element MIB Specification (RFC 2837)/ Fibre Alliance MIB Specification (Version 4.0)/ Methodologies for Interconnects (FC-MI-2)/ Device Attach (FC-DA) • Fibre Channel Classes of Service: Class 2/ Class 3/ Class F (inter-switch frames) connectionless Fibre Channel protocol support • NPIV support:FC-DA-2/ FC-MT/ FC-FS clause 5.2.41/ FC-LS table 141 clause 5.2.41/ 04-075v0/ 03-184v1/ 03-046 • External Customer Interfaces: Four external SFP+ Flex Ports which configure to assume either of the following identities/ 10 Gigabit Converged Enhanced Ethernet (CEE)/ 8/4/2 Gbps Fibre Channel • External Customer Interfaces Continued: RJ-45 Ethernet management port/ Unit power and system status LEDs/ Port login and activity 	

Accessory Product Details

LEDs/Recessed reset switch

- Media Support - Fibre Channel: Hot-pluggable/ 3.3 volt 8Gb SFP+ transceivers/ Also compatible with 4-Gbps and 2-Gbps SFPs/ Shortwave/ longwave optical
- Media Support - Ethernet: Hot-pluggable, 3.3 volt 10 Gigabit SFP+ transceivers/ TwinAx copper cables
- Other Features: SMI-S 1.1 support in firmware/ SAN boot support/Advanced Security (RADIUS, SSH, SSL)
- Diagnostics: Telnet/ Web browser interface/ SNMP (status only)/ Telnet/ CLI/ Web browser interface/ API interface
- Software/ Firmware Management Interfaces: Simple Network Management Protocol (SNMP)/ Management Information Base (MIB)/ CIM Provider/ Telnet/ CLI/Web Browser Management Interface/ API Interface
- Safety: USA/ Canada/ EU/ Australia/ New Zealand/ China

Services

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

HP 5800 Access Controller Module for 64–256 Access Points (JD441A)

Ports	1 RJ-45 out-of-band management port	
Physical characteristics	Dimensions	9.57(d) x 9.84(w) x 1.38(h) in. (24.3 x 25 x 3.5 cm)
	Weight	3.64 lb. (1.65 kg)
Memory and processor	Processor	Eight core @ 1000 MHz, 1 GB compact flash, 2 GB DDR2 SDRAM
Performance	Switch fabric speed	8 Gbps
	MAC address table size	8,000 entries
Environment	Operating temperature	32°F to 113°F (0°C to 45°C)
	Operating relative humidity	5% to 95%, non-condensing
	Non-operating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
Electrical characteristics	Non-operating/Storage relative humidity	5% to 95%, non-condensing
	Maximum heat dissipation	273 BTU/hr (288.02 kJ/hr)
Safety	Maximum power rating	80 W
	UL 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1; Anatel; GOST; C-Tick; NOM; IEC 60950-1 (with CB report)	
Emissions	EN 55022; VCCI; ICES-003; AS/NZS CISPR 22; EN 300 386; FCC Part 15; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC	
Immunity	EN	EN 61000-4-2:1995+A1:1998+A2:2001; EN 61000-4-3:2006; EN 61000-4-4:2004; EN 61000-4-5:2006; EN 61000-4-6: 1996 +A1:2001:A2:2007; EN 61000-4-8:2001; EN 61000-4-11:2004; EN 55024:1998+ A1:2001 + A2:2003
Management	IMC - Intelligent Management Center; command-line interface; Web browser; configuration menu; SNMP Manager; Telnet; HTTPS; RMON1; FTP; in-line and out-of-band; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB	
Notes	Max. number of users: 4K. Max. number of users that are supported by local authentication: 1K. Max. number of SSIDs that can be configured: 256. Max. number of users that are supported by local portal authentication: 2K. Number of ACLs: 8K.	
Services	Refer to the HP website at: www.hp.com/networking/services for details on the service-level	

Accessory Product Details

descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

General protocols

RFC 768 UDP
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet checksum
RFC 1144 Compressing TCP/IP headers for low-speed serial links
RFC 1256 ICMP Router Discovery Protocol (IRDP)
RFC 1321 The MD5 Message-Digest Algorithm
RFC 1334 PPP Authentication Protocols (PAP)
RFC 1350 TFTP Protocol (revision 2)
RFC 1812 IPv4 Routing
RFC 1944 Benchmarking Methodology for Network Interconnect Devices
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2104 HMAC: Keyed-Hashing for Message Authentication
RFC 2246 The TLS Protocol Version 1.0
RFC 2284 EAP over LAN
RFC 2644 Directed Broadcast Control
RFC 2864 The Inverted Stack Table Extension to the Interfaces Group MIB
RFC 2866 RADIUS Accounting
RFC 2869 RADIUS Extensions
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3619 Ethernet Automatic Protection Switching (EAPS)
draft-ietf-capwap-protocol-specification-00.txt:CAPW
AP Protocol Specification
draft-ohara-capwap-lwapp-03.txt:Light Weight Access Point Protocol

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2934 Protocol Independent Multicast MIB for IPv4

MIBs

RFC 1229 Interface MIB Extensions
RFC 1643 Ethernet MIB
RFC 1757 Remote Network Monitoring MIB
RFC 2011 SNMPv2 MIB for IP
RFC 2012 SNMPv2 MIB for TCP
RFC 2013 SNMPv2 MIB for UDP
RFC 2571 SNMP Framework MIB
RFC 2572 SNMP-MPD MIB
RFC 2613 SMON MIB
RFC 2863 The Interfaces Group MIB
RFC 2932IP (Multicast Routing MIB)
RFC 2933 IGMP MIB

Mobility

IEEE 802.11a High Speed Physical Layer in the 5 GHz Band
IEEE 802.11b Higher-Speed Physical Layer Extension in the 2.4 GHz Band
IEEE 802.11d Global Harmonization
IEEE 802.11g Further Higher Data Rate Extension in the 2.4 GHz Band
IEEE 802.11i Medium Access Control (MAC) Security Enhancements
IEEE 802.11n WLAN Enhancements for Higher Throughput

Network management

RFC 1155 Structure of Management Information
RFC 1905 SNMPv2 Protocol Operations
RFC 2573 SNMPv3 Applications
RFC 2574 SNMPv3 User-based Security Model (USM)
RFC 2575 VACM for SNMP
SNMPv1/v2c

QoS/CoS

RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2475 DiffServ Architecture
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 3394 Advanced Encryption Standard (AES) Key Wrap Algorithm
RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP)
Access Control Lists (ACLs)
Guest VLAN for 802.1x
MAC Authentication
Secure Sockets Layer (SSL)
SSHv1.5 Secure Shell

Accessory Product Details

IPv6

RFC 1350 TFTP
RFC 1881 IPv6 Address Allocation Management
RFC 1887 IPv6 Unicast Address Allocation Architecture
RFC 1981 IPv6 Path MTU Discovery
RFC 2292 Advanced Sockets API for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2375 IPv6 Multicast Address Assignments
RFC 2460 IPv6 Specification
RFC 2461 IPv6 Neighbor Discovery
RFC 2462 IPv6 Stateless Address Auto-configuration
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 2526 Reserved IPv6 Subnet Anycast Addresses
RFC 2563 ICMPv6
RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only)
RFC 3484 Default Address Selection for IPv6
RFC 3587 IPv6 Global Unicast Address Format
RFC 4443 ICMPv6
RFC 4541 IGMP & MLD Snooping Switch
RFC 4861 IPv6 Neighbor Discovery
RFC 4862 IPv6 Stateless Address Auto-configuration
RFC 5095 Deprecation of Type 0 Routing Headers in IPv6

SSHv2 Secure Shell
Web Authentication
WPA (Wi-Fi Protected Access)/WPA2

IKEv1

RFC 3748 - Extensible Authentication Protocol (EAP)

Summary of Changes

Date	Version History	Action	Description of Change:
May 29, 2015	From Version 24 to 25	Changed	Removed Rule 4 from Rack Level CTO Section Only on the Configuration Section
March 20, 2015	From Version 23 to 24	Changed	A to B Product Roll on the Switch Series, Features and benefits Technical Specifications and Configuration sections were updated. Overview and Technical Specifications were updated Accessories Section updated
July 3, 2014	From Version 22 to 23	Changed	Configuration menu updated.
June 10, 2014	From Version 21 to 22	Changed	Switch Options were revised in Configuration.
March 19, 2014	From Version 20 to 21	Changed	Fan Trays were revised in Configuration.
February 17, 2014	From Version 19 to 20	Changed	Transceivers were revised.
January 16, 2014	From Version 18 to 19	Changed	Notes were revised throughout Configuration and Configuration AF Model and External Redundant Power Supplies and Options for the HP RPS1600 Redundant Power System were added to Configuration SF Model.
November 22, 2013	From Version 17 to 18	Changed	Configuration was completely revised.
October 31, 2013	From Version 16 to 17	Changed	Configuration AF Model was completely revised.
October 9, 2013	From Version 17 to 18	Changed	Configuration was completely revised.
October 31, 2013	From Version 16 to 17	Changed	Configuration AF Model was completely revised.
October 9, 2013	From Version 15 to 16	Removed	HP X124 1G SFP LC SX and HP X124 1G SFP LC LX Transceivers were removed.
September 11, 2013	From Version 14 to 15	Changed	Minor edit was made in Configuration
August 19, 2013	From Version 13 to 14	Changed	Notes sections were revised in Configuration
June 21, 2013	From Version 12 to 13	Changed	HP 5820AF-24XG Switch was revised in Configuration
June 10, 2013	From Version 11 to 12	Removed	Accessory Product Details: Removed Hp 0.5 - 50 m PremierFlex OM3+LC/LC Optical Cables.
		Added	Added Configuration and Configurations AF Model sections.
		Changed	Accessories: Updated HP 5820 Switch Series accessories section.
August 24, 2012	From Version 9 to 11	Changed	Updated the Features and Benefits, Introduction and Accessories sections.
March 22, 2012	From Version 8 to 9	Changed	The formatting in one of the models in Specifications was updated.
November 16, 2011	From Version 7 to 8	Changed	Specifications were revised.
September 30, 2011	From Version 6 to 7	Added	Accessory Product Details was added.

Summary of Changes

September 26, 2011	From Version 5 to 6	Changed	Accessories was revised, a new model was added, and the verbiage in the other models, as well as the Features and Benefits section was updated.
September 20, 2011	From Version 4 to 5	Changed	Accessories was revised.
May 9, 2011	From Version 3 to 4	Changed	Accessories was revised.
April 19, 2011	From Version 2 to 3	Changed	Accessories was revised.
March 16, 2011	From Version 1 to 2	Changed	Monitor and Diagnostics was revised.

Summary of Changes

To learn more, visit: <http://www.hp.com/networking>

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.